



Operating Manual

# FRANKA RESEARCH 3

## TABLE OF CONTENTS

© Copyright 2025  
Franka Robotics GmbH  
Frei-Otto-Straße 20  
80797 Munich  
Germany

The information in this document, including any extracts, may only be reproduced or shared with third parties with the explicit authorization of Franka Robotics GmbH.

The content of this document has been carefully checked against compliance with the hardware and software described. However, discrepancies cannot entirely be ruled out, which is why we assume no liability for complete compliance.

In the interest of our customers, we reserve the right to make improvements and corrections to hardware, software, and documentation at any point in time without notice.

We are always grateful for your feedback at documentation@franka.de.

The English documentation is the ORIGINAL DOCUMENTATION. Other languages are translations of the original document.

Complementary documents for this operating manual are:

- Datasheet Franka Research 3 (Document number: R02212)
- ESD Measurements FR3 (Document number: R02015)
- Quick Guide for Installation FR3 (Document number: R02040)
- Hardware Manual Franka Research 3 (Document number: R02210)

Document name: Operating Manual Franka Research 3

Document number: R02216

Release Version: System image version 5.6.0

Change Log:

Content Iteration	Release Date	Release notes / Changes
1.0	October 2025	Release of the Operating Manual for system image version 5.6.0
1.0.1	December 2025	Corrected LED color reference table in chapter 13.6



Get your manual and additional supporting material in English and other languages at [www.franka.de/documents](http://www.franka.de/documents).

# TABLE OF CONTENTS

TABLE OF CONTENTS .....	3
1 ABOUT THIS MANUAL .....	7
1.1    1.1 Software and hardware version .....	7
1.2    1.2 Applicable document .....	7
2 SAFETY INSTRUCTIONS AND GENERAL INDICATIONS .....	8
3 GETTING STARTED .....	9
3.1    Initial setup .....	9
3.1.1    Connecting a user interface device .....	9
3.1.2    Hardware recommendation .....	9
3.1.3    Procedure .....	9
3.1.4    Initial configuration – “First Start” .....	10
3.2    Unexpected motions during guiding .....	14
3.3    Falling objects during installation .....	14
3.4    End effector configuration .....	14
4 TYPICAL USAGES .....	15
5 WORKING WITH FRANKA RESEARCH 3 .....	16
5.1    Robotic basics .....	16
5.2    Single point of control (SPoC) .....	17
5.2.1    Take control .....	17
5.2.2    Request control .....	18
5.2.3    Enforce control .....	19
5.2.4    Release control .....	20
5.2.5    Fieldbus control .....	20
5.3    Operating modes .....	21
5.3.1    Programming .....	22
5.3.2    Execution .....	23
5.4    Apps .....	28
5.5    Creating a Task .....	28
5.6    Task settings .....	29
5.7    Parameterization of Apps .....	29
5.8    Pose teaching .....	31
5.9    Pose fine adjustment .....	32
5.10    Guiding configurations .....	32
5.11    Necessary guiding components .....	34
5.12    Guiding .....	35

## TABLE OF CONTENTS

5.13	Editing end effector settings .....	36
6	FRANKA UI.....	38
6.1	Login .....	38
6.1.1	Elements .....	38
6.2	Desk.....	39
6.2.1	Overview .....	39
6.2.2	Elements .....	40
6.3	Watchman.....	42
6.4	Settings Interface .....	43
6.4.1	Elements .....	44
7	ROLES AND PERSONNEL.....	45
7.1	Personnel .....	45
7.1.1	Responsible person.....	45
7.1.2	User .....	45
7.1.3	Integrator.....	45
7.2	User Roles .....	46
7.2.1	Operator.....	46
7.2.2	Administrator.....	46
7.2.3	Safety operator .....	46
7.2.4	Assigning user roles.....	47
8	MANAGING FRANKA RESEARCH 3.....	48
8.1	Managing Apps and Updates .....	48
8.2	Hub.....	49
8.3	Updates.....	49
8.4	Backup .....	50
8.5	Safety Configuration .....	51
8.6	Network Setting.....	51
8.7	Modbus Configuration .....	52
8.8	End Effector Configuration .....	52
8.9	Saving of the created Tasks .....	53
8.10	Franka World .....	53
9	TROUBLESHOOTING.....	54
9.1	General use .....	54
9.1.1	Recoverable errors .....	54
9.1.2	Arm pulls strongly in one direction during teaching.....	54
9.1.3	Loud clicking at switch-off .....	55
9.1.4	Joint limit error .....	55
9.1.5	Joint position error.....	56

## TABLE OF CONTENTS

9.1.6	Failed to unlock joints.....	61
9.1.7	Robot does not finish booting.....	61
9.1.8	Desk continuously displays “Shutting down the system” .....	61
9.1.9	Robot does not boot after turning on the Control.....	61
9.1.10	Restarting after an unexpected stop.....	62
9.2	Troubleshooting while using FCI .....	62
10	ADVANCE CONTROL .....	62
10.1	Franka Control Interface (FCI).....	62
10.2	Working in principle with the FCI interface .....	63
10.3	Setup of Franka Control Interface (FCI).....	66
10.3.1	Network Configuration for FCI .....	67
10.3.2	Static IP Configuration Example.....	67
10.3.3	Configuring Control’s Network .....	68
10.3.4	Configuring the Operating Device (Ubuntu 20.04).....	68
10.4	Setup of libfranka on a Linux workstation.....	69
10.5	Verification of communication.....	74
11	SAFETY CONCEPT .....	76
11.1	Safety Functions.....	76
11.2	Other safety-related recoveries (in case of safety errors).....	80
12	SAFETY CONFIGURATION/WATCHMAN.....	81
12.1	Watchman.....	81
12.1.1	Overview .....	81
12.2	Safety Configuration .....	83
12.2.1	Adjusting predefined scenarios and rules .....	83
12.2.2	Safety Scenarios for states in Programming mode.....	83
12.2.3	Safety Scenarios for states in execution mode .....	84
12.2.4	Error/Violation states.....	84
12.2.5	Editing of the Safety Configuration .....	86
12.3	Import/Export of Safety Settings.....	87
12.3.1	Import Procedure .....	89
12.3.2	Export Procedure .....	90
12.3.3	Safety Setup .....	92
12.3.4	General Safety Settings.....	92
12.3.5	Safe Input Configuration .....	92
12.3.6	End Effector Configuration .....	92
12.3.7	Creation of spheres for modelling an End effector envelope.....	93
12.3.8	Creating and editing rules .....	95
12.3.9	Structure of a rule.....	96

## TABLE OF CONTENTS

12.3.10	Validate.....	99
13	ROBOT LED INDICATOR SYSTEM .....	103
13.1	Overview of the status indicators .....	103
13.2	LED Activation Behavior .....	104
13.3	Startup Checklist for Operators .....	104
13.4	Flashing Patterns.....	104
13.5	LED Priority Logic.....	105
13.6	LED Color Reference Table.....	105
14	SERVICE AND SUPPORT.....	108
14.1	Rescue System .....	108
14.2	Log download.....	111
14.3	Available log files and how to download them .....	111
14.4	Downloading log data .....	112
14.5	Hardware Exchange.....	113
14.6	Replacing the Control .....	113
14.7	Transportation pose of the Arm.....	116
14.7.1	Procedure.....	116
15	INDEX.....	117
16	TABLE OF FIGURES.....	119

# 1 ABOUT THIS MANUAL

This operating manual gives the information that you need to operate and handle the **Franka Research 3 (FR3)** robot system in a safe and correct way.

This manual includes:

- Instructions for the initial setup
- Information about hardware and software configuration
- Descriptions of typical use cases
- Instructions to use the Franka UI, apps, and the Franka Control Interface (FCI)
- Safety instructions
- Managing apps and updates
- Troubleshooting steps
- Advanced configuration procedures

Use this manual during installation, operation, and maintenance of the FR3 robot system.

## 1.1 Software and hardware version

This manual applies to system image version 5.6.0.

This version is compatible with all versions of the FR3 robot.

## 1.2 Applicable document

In addition to this manual, the following document also applies:

- **Hardware Manual:** Franka Research 3 with Arm v2.0.
- **Hardware Manual:** Franka Research 3 with Arm v1.
- **Document number:** R02210

## 2 SAFETY INSTRUCTIONS AND GENERAL INDICATIONS

### Warning notices

Before installing, starting up, and operating the device, carefully read this manual and any additional documentation. Take NOTICE of the safety instructions as well as general indications.

Warning notices are posted as follows:

#### CAUTION

- Type of hazard
- Potential consequences of hazard
- Evasive/avoidance actions to be taken

The following warning notices are used in this manual:

#### DANGER

DANGER indicates a hazardous situation that, if not avoided, will result in death or serious injury.

#### WARNING

WARNING indicates a hazardous situation that, if not avoided, could result in death or serious injury.

#### CAUTION

CAUTION indicates a hazardous situation that, if not avoided, could result in minor or moderate injury.

#### NOTICE

NOTICE indicates information considered important but not hazard related.

#### SAFETY- INSTRUCTION

SAFETY INSTRUCTION indicates processes that need to be strictly observed.

## Indications



Indicates where further information can be obtained.

Franka Research 3 is equipped with a comprehensive safety system designed to meet application-specific requirements and international safety standards. For an overview of the system architecture, safety functions, and configuration using the Watchman tool, ***please refer to the chapter 10 titled "Safety Concept" in this Manual.***

For additional safety measures and potential hazards, ***refer to Chapter 4 "Safety" in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).***

# 3 GETTING STARTED

## 3.1 Initial setup

### 3.1.1 Connecting a user interface device

An external operating device in the form of a PC, laptop, or tablet is required to operate and control the robot.

### 3.1.2 Hardware recommendation

- Commercially available PC, laptop, or tablet
- Ethernet interface
- Resolution: minimum 1280x720px, recommended Full HD (1920x1080 px)
- Multitouch function (if using a tablet)
- Recommended browsers: Chrome, Edge, Safari, or Firefox

### 3.1.3 Procedure

1. Connect the interface device to the X5 connector on the Arm base via Ethernet cable to open the initial configuration interface.

#### NOTICE

***For more information, please refer to chapter 7 section 7.6 Wiring and Electrical Installation in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).***

2. Ensure your interface device has DHCP client activated to automatically obtain the IP address.  
The IP address will be assigned once Franka Research 3 is powered on.

3. Open your preferred web browser.

4. Enter the following URL: `robot.franka.de`

5. Press **\*\*Enter\*\***.

The website showing the Franka UI opens up.

### 3.1.4 Initial configuration – “First Start”

After starting the Control for the first time, basic system settings must be configured.

This configuration is displayed in the web browser and also appears after resetting the Control to factory settings.

1. Start Franka Research 3.
2. Enter the following URL: [robot.franka.de](http://robot.franka.de)
  - ⇒ The "First Start" web interface of the Franka UI opens with the language selection of the system interface.




Figure 1: language selection initial configuration

3. Click on the area where the IP address of the robot is shown in the menu bar to download the manual. Be sure to read it carefully.
4. Select the desired language for the Franka UI interface. Click on „NEXT“
  - ⇒ The page for setting the network connection is opened.




Figure 2: Network

On this page, the network connections of the internal robot network and those of the Internet connection or connection to a company network can be configured.

## GETTING STARTED

The subaddress of the robot network can be adjusted if required. The default setting is 192.168.0.1, the address range can be used from 100-150.

For access to the company network or the Internet, the use of the DHCP client can be selected or a manual configuration can be performed.

The current connection status to Franka World is displayed graphically.

5. Confirm the settings by clicking on „NEXT“

⇒ The web interface for configuring / managing the robot with Franka World opens.




Figure 3: Franka World registration

This page is used to register the robot in Franka World and to manage updates and Apps.

When the Control is connected to the Internet, the robot is automatically registered in Franka World and checked for the availability of the latest system updates or application software (Apps).

The configuration of the robot is done in Franka World. You can open Franka World by clicking on the link.

A Franka World account is required for installing system updates and Apps refer to Chapter 7.1, Managing apps and updates.

6. Click on „Download“ to transfer any available changes.

If an internet connection cannot be established, you can also update the device "offline". For this purpose, read chapter 8.3 „Updates“.

7. After the data has been transferred, confirmation is required to complete the installation. To do this, click on "Apply".

A restart will be initiated in case of system-relevant changes. The first-start procedure is then restarted, but your previous settings are stored. In this case, confirm all previous steps with "Next".

After all available changes have been installed in the Franka World step, you can proceed to the next step by clicking "Next".



For information about system updates und Apps, see chapter 8.1 "Managing Apps and Updates".

⇒ The web interface for creating the administrator is opened.




Figure 4: Creating Administrator

8. Create an initial user of type "Administrator"

This user can continue the configuration later and create additional system users. For more information on roles, see the section "Creating an administrator" in Chapter 7 "ROLES AND PERSONNEL".

9. Confirm the input by clicking on „Next“.

⇒ The web interface for configuring the end effector is opened.




Figure 5: End effector settings

**⚠️ WARNING****Unexpected motions during guiding due to incorrectly configured end effectors**

Incorrectly configured end effector mass and inertia may lead to not entirely compensated gravitational forces. The resulting and unexpected behavior of the robot including end effector may lead to injuries such as crushing, tearing of the skin, and puncturing.

- Always check the configuration of the end effector.
- When copying an already parametrized App or Task to another Franka Research 3 system, ensure that the end effector configuration remains identical to the original one.

**⚠️ CAUTION****Falling objects from end effectors during initial installation**

Objects falling from the gripper lead to injuries to hands, fingers, feet, and toes.

- Always wear personal protective equipment (e.g., safety shoes).
- Use the appropriate type of grippers to prevent objects from falling.
- Consider the shape, texture, and weight of the grasped objects in the risk assessment according to 10218-2. Using lightweight and/or round objects may reduce risks significantly.
- Do not place your hands between grasped and solid objects (e.g., table).
- Do not load the end effector before start-up, since depending on the installed end effector, the 'homing' motions may be executed automatically upon restoration of power.

10. Configure which end effector is used on the robot.

If you do not have an end effector mounted, select **“None”** from the drop-down menu. .

If you have mounted Franka Hand as an end effector, select **“Hand”** from the drop-down menu.

**NOTICE**

Franka Hand is not part of the certified robot.

If you want to use another end effector or adjust the configuration of the Hand, select “User Defined” from the dropdown and enter the corresponding values into the text fields. The appropriate values are usually found in the end effector’s manual.

**NOTICE**

You will be able to reedit the end effector settings later on.

11. Confirm the entries by clicking on “Confirm”. The initial configuration is thus completed and confirmed, and a final preparation step is performed.

- ⇒ The programming interface DESK is displayed in the web browser and the status display on the Arm lights up permanently in blue.

## 3.2 Unexpected motions during guiding

Incorrectly configured end effector mass/inertia may lead to unexpected robot behavior and injuries.

- Always check end effector configuration.
- Ensure configuration consistency when copying Apps/Tasks between systems.

## 3.3 Falling objects during installation

Objects falling from the gripper may cause injuries.

- Wear personal protective equipment (e.g., safety shoes).
- Use appropriate grippers.
- Consider object shape, texture, and weight in risk assessment.
- Avoid placing hands between grasped and solid objects.
- Do not load the end effector before start-up.

## 3.4 End effector configuration

- If no end effector is mounted, select \*\*None\*\*.
- If Franka Hand is mounted, select \*\*Hand\*\*.
- For other end effectors, select \*\*User Defined\*\* and enter values from the manual.

### NOTICE

- Franka Hand is not part of the certified robot.
- You can re-edit end effector settings later.

## 4 TYPICAL USAGES

After switching on the robot, the **Franka UI** must be accessed via:

- The previously assigned IP address, or
- robot.franka.de (if the operating device is connected to the **X5 – Robot network** on the robot base)

Franka Research 3 can be controlled in two different ways:

### 1. Control via Apps in Franka UI

You can control and program the robot using **Apps** directly in the open **Franka UI**.

For further explanations and operating instructions, refer to the see Chapter 5 “Franka UI”.

### 2. Control via Franka Control Interface (FCI)

To control the robot using the **Franka Control Interface (FCI)**:

1. Open **Desk** in the Franka UI.
2. Expand the **System** menu in the header.
3. Change the operation mode to **Execution**.
4. Press the **Activate FCI** button to enable the FCI interface.

Once activated, you can control the robot via:

- Linux terminal using **libfranka**
- **ROS, ROS 2, or MATLAB** interfaces

#### NOTICE

##### Network Requirements for FCI Mode

- The robot must be connected to the operating device via the **C2 – Shop Floor network** on the front of the Control unit.
- A **stable and fast network connection** is required.
- **FCI mode cannot be used** when the robot is connected via the **X5 – Robot network** on the robot foot.

# 5 WORKING WITH FRANKA RESEARCH 3

## 5.1 Robotic basics

### Joint space

In joint space, a robot pose is described using the rotation angles of each of the robot's joints. In contrast to most industrial robots, which have six joints, Franka Research 3 has seven joints. This allows for extremely high flexibility. A linear movement of the end effector on the robot through space results from the superimposed interaction of the rotation of several joints.

### Cartesian space

In Cartesian space, a robot pose is not described by the rotation angles of the individual robot joints but is specified with relation to the reference coordinate system (world coordinate system of the robot or tool coordinate system). Here, the position and orientation of the end effector are the focus. The three-dimensional space representation of a Cartesian pose usually consists of three values of lengths (in meters) for determining the position and three values (in degrees) for the orientation of the end effector.

Movements in Cartesian space allow the precise tracking of predefined paths in space, such as straight lines. The changing of position is called translation, while the changing of orientation is called rotation. The Cartesian motion of a robot always depends on the reference coordinate system, which can be configured for Franka Research 3 via the configuration of the end effector in the administration's settings of Franka UI.

### Redundancy

As Franka Research 3 has seven joints, the Arm can reach a certain Cartesian pose with various joint configurations. This capability is called redundancy. The part of the robot that can still be moved while keeping the end effector pose the same is often called 'elbow' because it matches the motion capability of the elbow in a human arm. The redundancy of the Arm allows for greater flexibility when teaching or executing tasks, e.g., using it to circumnavigate an obstacle to grip an object located behind it. The behaviour of the robot's elbow can be changed and adapted to each situation. It can be set to freely movable or immovable.

### Sensitivity

The Arm has torque sensors in all seven joints. The torque sensors enable, among other things, to recognize and react to even the smallest forces acting on the Arm. This sensitivity facilitates numerous functionalities and capabilities, such as impedance or sensitive collision detection. For achieving maximum sensitivity, the robot system must be adapted in the best possible way to the additional masses attached to and picked up by the robot. For this reason, the end effector must be configured as precisely as possible in the Franka UI settings.

### Impedance

Impedance is a robot's behaviour that imitates the ability of a mechanical spring. An impedance-controlled robot can interact gently with the environment, e.g., to not damage fragile objects. The ability to change impedance can be seen as similar to that of a human arm, which tenses the muscles to change rigidity and can adapt depending on the situation to increase robustness when executing a task.

### Collision detection and reaction

Torque sensors have been incorporated into all seven axes. These provide information on the currently applied torques per axis at any given time. In combination with our model-based Control of Franka Research 3, contact forces and torques of the joints can be precisely determined. Then, the Arm can respond. For example, if the Arm touches an unexpected

object while moving, this contact is detected in real time by one or more torque sensors and classified as a collision. This can then be used, for example, to stop the movement of the robot.

**NOTICE**

The robot's reaction to collisions depends on the users programming and is not a safety feature.

## Generating forces

The Arm is in intended contact with its surroundings. With the help of the torque sensor signals, a defined force on the point of contact can be generated by the motors. To achieve this, suitable apps or programming are required.

**NOTICE**

External wiring adds additional loads and torques to the Arm which may influence the Franka Research 3's control performance.

## 5.2 Single point of control (SPoC)

Franka Research 3 provides **\*\*Single Point of Control (SPoC)\*\*** functionality to comply with safety and regulatory standards.

This ensures that only one user at a time can trigger critical actions such as:

- Editing system settings and tasks
- Unlocking joints
- Running tasks

The user in control is assigned the **\*\*SPoC software token\*\***.

SPoC also applies to **\*\*Fieldbus interfaces\*\***

**NOTICE**

Even without the SPoC token, it is still possible to trigger uncritical actions like stopping a running Task or locking the robot brakes.

### 5.2.1 Take control

When connecting to the robot with an available token, take control by accepting the dialog displayed after login. The token is now assigned to you. Other users cannot control the robot without your consent.

## 5.2.2 Request control

When connecting to the robot with a token already taken by another user, request control by accepting the dialog displayed after login. The controlling user will be shown a control request dialog on the screen. The token is reassigned to the requesting user if the controlling user grants access. If the controlling user denies access, the token will remain with the controlling user.

### NOTICE

For improved traceability, it is recommended to set up named profiles for each user in the system settings. That way, the system is able to inform newly connected users about who is currently controlling the robot.

A user requests control:




Figure 6: Control request




Figure 7: User management waiting for approval

The user who has the SPoC token receives the control request:




Figure 8: User request

### 5.2.3 Enforce control

It is possible to enforce control if the user has physical access to the robot. Instead of requesting control, the user chooses to enforce control in the dialog displayed after login. After choosing enforced control, the requesting user has a time window in which he can press the blue circle on the robot's Pilot to take control. The controlling user is notified about the enforcement attempt during this time frame. The controlling user is then able to confirm or deny control.

#### NOTICE

Adjust the time window for control enforcement in the system settings. By default, the time window is set to 30 seconds.

New user enforces control:




Figure 9: Enforce control

## 5.2.4 Release control

After the controlling user has finished working with the robot, the controlling user can release control in the robot menu. This will lock access to the controlling user and release the token. Other users can now connect to the robot and take control directly. Control is also released if the controlling user logs out.

## 5.2.5 Fieldbus control

It is also possible to control the robot through Fieldbus interfaces. Single-Point-of-Control also applies to Fieldbus interfaces. The required functionalities are provided for the supported Fieldbus protocols but must be considered during connection implementation. Data access and uncritical actions are possible via Fieldbuses regardless of the token status.

Franka Research 3 implements OPC UA server functionality.

### NOTICE

All Fieldbuses have the same rights as the operator role.

### NOTICE

If the robot is controlled via a Fieldbus protocol, there is no request procedure for other users trying to take control via Franka UI. When a Franka UI user takes control, the token is automatically reassigned from the Fieldbus protocol towards the user.



For more information on how to use Modbus and OPC UA, see the respective manual at Franka World.

## 5.3 Operating modes




Figure 10: Overview operating modes

Franka Research 3 offers the following operating modes:

1. Programming
  - Idle (default)
  - Teach a Task (Enabling Button, Guiding Button)
  - Test & Jog (External Enabling Device, Hold-to-run button in Desk)
2. Execution
  - Work (default)
  - Monitored stop
  - Assist (Enabling Button, Guiding Button)

## Switching

Switch between the general "Programming" and "Execution" modes using the toggle button in the Desk sidebar. Certain user interactions select all other modes implicitly within the general modes, e.g., pressing the External Enabling Device in "Programming."

The general operating modes can also be switched via Fieldbus control.

### 5.3.1 Programming

Programming mode is an operating mode in which the robot can be programmed to execute certain Tasks.

Controlling the robot via FCI is not possible in "Programming" mode.

#### 5.3.1.1 Teach a Task (Guiding Enabling Device)

The administrator teaches the robot by parameterizing the Task and its Apps. This is done by hand-guiding the robot with the Enabling and Guiding Buttons at the Pilot-Grip.

#### 5.3.1.2 Test & Jog (External Enabling Device)

The administrator tests and monitors the execution while standing back from the robot. The External Enabling Device connected to the robot via the dedicated X4 port is used.

#### 5.3.1.3 Typical procedure for programming

Proceed as follows when programming with the Franka Research 3:




Figure 11: Procedure

1	Teach a Task	3	Run a Task
2	Test & Jog		

#### Teach a Task (1)

Teach Franka Research 3 a Task.

#### Test & Jog (2)

Step out of the maximum workspace and check whether the taught Task is correctly executed. For this, the velocity can be limited, and the execution can be stopped at any time.

## Run a Task (3)

Once the Task has been taught, Franka Research 3 executes the Task automatically.

### 5.3.2 Execution

Execution mode is an operating mode in which the robot executes the tasks previously taught via the Franka UI or can be moved via the Franka Control Interface.

#### 5.3.2.1 Work

In Work mode, automatic execution of Tasks without the requirement of safe External Enabling Devices is activated.

In Work mode, the robot executes its task autonomously. Compared to Test & Jog, there is no External Enabling Device as a safeguard, i.e., the operator needs to be safely separated from dangers presented by the Arm (acc. to EN ISO 10218-1:2011 and ISO 10218-2).




Figure 12: Area assignment

1	Maximum workspace	3	Perimeter safeguarding
2	Safeguarded space		

Precondition

- A Task has been created in Teach a Task
- The Task has been successfully tested in Test & Jog.
- The safety system is running without violations and errors.

#### NOTICE

Always evaluate the remote start of the execution and realize the safety concept within the safety design (e.g., external safety means) and the safety settings of the robotic system.




Figure 13: Work operation

**NOTICE**

Noise levels during operation < 70 dB (A)

**Procedure**

1. Switch to the “Execution” operating mode
2. Press the Play Button in Desk.

*A confirmation dialog is shown.*

3. Confirm the dialog.

*The robot executes the learned task.*

**NOTICE**

If a collision occurs, the execution is stopped. The failed App is highlighted, and an error description is displayed. In this mode, the Arm can be moved using guiding and any causes of error can be eliminated.

**NOTICE**

Any error message is displayed in the sidebar. There, information on the error and how to eliminate it can be viewed.

1. To continue with the execution, press the Play button for one of the Apps.
2. To end the Task, press the Stop button.

**NOTICE**

The remote execution start must be evaluated during the realization of the specific cell safety concept.

## Requirements for using the Franka Control Interface (FCI)

- Der FCI-Mode is activated (see 4 "TYPICAL").
- A network connection exists with the Linux workstation.
- The safety system operates without violations and errors.
- Brakes are open.
- The control system is in Execution mode.

**NOTICE**

In the event of an error during control via FCI, the current operation is aborted and the resulting error is transmitted via the FCI. In Franka UI an error message is shown.

The user's program must now be designed so that the errors are automatically transmitted as output.

### 5.3.2.2 **Monitored stop**

The robot is at a supervised standstill. This mode is present in the following cases:

A safety sensor connected to a safe input configured in a dedicated safety rule using the SMSS safety function detects the presence of a human.

A transition mode to offer Assist mode to the user.

### 5.3.2.3 **Assist**

This mode can be used during execution if hand-guiding is part of the application. This mode is only permitted within the collaboration space defined.




Figure 14: Assist operation

**⚠️ WARNING**
**Hot Surfaces and Guiding**

At ambient temperatures above 30 °C the robot surface can become too hot to touch. Therefore, using the Assist feature in Execution mode is not permitted above 30 °C

The Assist mode is a state of the Execution operating mode. This mode enables collaborative operation with manual guidance in accordance with ISO 10218-1. In order for it to be usable, this mode must be explicitly enabled by a safety operator in Watchman.

If the robot is placed in Save Monitored Standstill (SMSS) during the execution of a task, the robot automatically switches to Assist Mode when the Enable and Manual Guidance buttons are pressed. This state is displayed in the robot's status message in DESK.




Figure 15: Indication of Assist Mode

In this mode, the operator can move the robot in manual control by pressing the Enabling Button on the robot's Pilot-Grip.




Figure 16: Conditions for motion enabling in Assist Mode

### ⚠️ WARNING

#### Hot Surfaces and Guiding

At ambient temperatures above 30 °C the robot surface can become too hot to touch. Therefore, using the assist feature in automatic mode is not permitted above 30 °C.

If the **Safely Monitored StandStill** condition (SMSS) is removed again, the robot resumes execution of the stopped task and moves to the next pose.

When using the Franka Control Interface (FCI), an error message is issued by the SMSS and the execution of the robot movement is stopped. The cancellation of the SMSS does not automatically lead to a restart of the robot. This must be restarted via the command input.

#### Condition for initiating Assist Mode:

- Activated Assist-Mode in the Safety Settings in Watchman. This activation can only be done by a safety operator.
- The robot must be in **Safe Monitored StandStill** (SMSS). For this purpose, a rule must be created in the Work Scenario in Watchman that brings the robot into the safe monitored state (**Safe Monitored Stand Still**). The trigger for this rule can be the processing of a safe input signal (X3.2 or X3.3) or the entry into a defined safe space. It is recommended to initiate the triggering of the safe monitored standstill by a safe input signal.
- Press the Enabling Button and the Guiding Button.

#### Options for movements in Assist Mode:

- By pressing the Enabling and Guiding Buttons on the Pilot Grip, the robot can be moved freely in Hand Guiding mode.
- Movements of the mounted end effector are not enabled in Assist mode.

## Exiting the Assist Mode:

The Assist mode automatically stopped when the Enabling Button or the Guiding Button is released.

### CAUTION

If the **Safe Monitored StandStill (SMSS)** is triggered by a monitored space, the robot immediately moves to the next pose when the Enabling or the Guiding Button is released outside the monitored space. Therefore, plan a safe input (X3.2 or X3.3) for the use of the Assist Mode to initiate the **Safe Monitored StandStill (SMSS)**.

## 5.4 Apps

Apps incorporate the entire complexity of the Franka Research 3 system and represent modular building blocks of a process such as grasping, plugging, insertion, and screwing. Using Desk, Apps can be arranged to create entire Tasks in no time. The created Tasks can quickly be adapted, reused, or deployed on multiple robots to reduce set-up costs remarkably. Individual Apps and Tasks can be parameterized by teaching Franka Research 3 poses by demonstration or adding context-relevant parameters such as speed, duration, forces, and triggering actions.

### i

Visit our Store on <https://franka.world> to browse our continuously growing portfolio of Apps and solutions.

## 5.5 Creating a Task

### WARNING

#### Risk of injuries during guiding

Risk of tearing the skin or puncturing during guiding.

- Do not have sharp edges in the maximum workspace.
- Do not keep any pointed objects in the maximum workspace.
- *For more information, refer to Chapter 7.9 “Practical Tips for Usage and Positioning of Franka Research 3” in the respective Hardware Manual i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2.*

### NOTICE

Before executing any Task with Franka Research 3, make sure to read chapter “4.5” first.

### Procedure

1. To create and select a new Task, click on the "+"-symbol in Tasks and assign a name.

A new Task is created with an empty Timeline.

2. Drag and drop the respective Apps from Apps to Timeline to program an individual Task. Alternatively, double click on the respective Apps to add it to the timeline.
3. Arrange them in the desired sequence by dragging and dropping the Apps. The programmed Tasks are executed from left to right.
4. To remove Apps from a Task, drag and drop the respective Apps from Timeline to Apps. Alternatively, right-click on the App to open a drop-down menu from which you can activate, deactivate, or delete individual Apps.
5. To change Task-level settings, e.g., the execution speed, click on the Task name in Timeline.

## 5.6 Task settings

### Procedure

1. Click on the Task's name in the top left corner of Desk.
2. Set the parameters for robot speed, compliance/stiffness, and sensitivity thresholds.

#### NOTICE

Navigation and parameterization can also be done via buttons on the Pilot.

## 5.7 Parameterization of Apps

#### ⚠ WARNING

##### Falling objects from end effectors during initial installation

Objects falling from the gripper lead to injuries to hands, fingers, feet, and toes.

- Always wear personal protective equipment (e.g., safety shoes).
- Use the appropriate type of grippers to prevent objects from falling.
- Consider the shape, texture, and weight of the grasped objects in the risk assessment according to 10218-2. Using lightweight and/or round objects may reduce risks significantly.
- Do not place your hands between grasped objects and solid objects (e.g., table).
- Do not load the end effector before start-up, as "homing" might happen after each time brakes are unlocked upon power-up.

After the administrator creates a Task and adds at least one App, the App parameters can be configured.

## Precondition

- A Task has been created and selected to be shown in the Timeline.
- An App has been added to the Task.

## Procedure

1. To open an App in the created Task, click on it.  
*A corresponding context menu appears to set the parameters.*
2. Follow the instructions in the App context menu to teach or parameterize poses.
3. Hand-guide the robot to the desired pose.
4. Press the Teach button on the Pilot-Disc to confirm the pose.

For further information on guiding, see section Guiding configuration in chapter 4.7. The context menus of the Apps vary and contain one or more steps for entering parameters, e.g., teaching poses or entering execution speed.

Only activated Apps are executed and need to be taught.




Figure 17: App parameterization

### NOTICE

The Pilot (buttons) can also be used for navigation and parameterization.

## 5.8 Pose teaching

### ⚠ CAUTION

#### Unexpected movement of Arm

Incorrect set mass and center of gravity values may lead to injuries, such as crushing.

- Check the mass and center of gravity for any end effector and the objects grasped by it.
- Correct the values if necessary.

#### Precondition

An App with pose parameters has been added to the Task.

#### Procedure

1. Open App by clicking on it.




Figure 18: App interface

2. Click on necessary Step in the App

Guide the Arm as described in chapter 5.12 "Guiding"

3. Stop guiding the Arm.
4. Release the buttons when the correct pose is reached.
5. Confirm the pose by pressing the Teach button.

Teaching a pose in the App is now finalized.

## 5.9 Pose fine adjustment

### Procedure

1. Click the App in which you want to adjust the pose.

*The context menu appears.*

2. Right-click on the pose you want to adjust in the context menu.
3. Adjust the Cartesian pose of the end effector translationally and/or rotationally via the plus/minus keys (2) in single steps. When you have adjusted the pose, you can move the Arm to the readjusted pose via the "HOLD TO MOVE" (3) button.

The "TAKE LIVE POS" (4) button can be used to adopt the pose previously achieved by manual guidance and the "TAKE STORED POSE" (5) button can be used to adopt the pose currently stored in the Control as the current configuration.

4. To save the pose, click on „SAVE“ (1).

*The pose is adjusted.*




Figure 19: Pose fine adjustment

## 5.10 Guiding configurations

In Guiding mode, the motion of the Arm follows the corresponding guiding configuration, which is displayed in the sidebar. The guiding configuration can be changed by pressing the Guiding-Mode Button on top of the Pilot-Grip. The desired configuration can also be selected from the sidebar. The following configurations can be selected:

- Translation

The Arm can only be moved to change the Cartesian position of the end effector. Its orientation remains as it was before entering the Guiding mode.

- **Rotation**

The Arm can only be moved to change the Cartesian orientation of the end effector. Its position remains as it was before entering the Guiding mode. The reference coordinate system for this rotation is the predefined coordinate system of the end effector.

- **Free**

The Arm can be moved freely. All seven joints can be moved.

- **User**

The user can define the guiding behavior for each Cartesian translation and rotation axis. The elbow can be movable or fixed.




Figure 20: Overview of switching between Hand-Guiding-Modes



Figure 21: Illustration of Hand Guiding

If “User mode” is selected, the user can select constraints for guiding:




Figure 22: Settings, if "User mode" is selected

## 5.11 Necessary guiding components

To guide the Arm, use the Pilot.

**NOTICE**

Operate Desk directly via the touchscreen or using your mouse/keyboard.

**NOTICE**

The motion speed in Teach or Hand Guiding-Mode is pre-set. In the settings of Watchman, the speed can be reduced according to the risk evaluation of the Arm within its application.

### Safety instruction

#### Precondition

1. The Control must be switched on and booted up.
2. All external devices connected to X3 must be allowed to move.
3. Emergency stop is released.

#### Procedure

- Leave the maximum workspace and make sure that no other people are within the maximum workspace.
- On Desk, click on "Unlock joints".

*Each of the seven axes makes a small movement and seven clicking noises can be heard.*

*The Arm is now in idle mode or monitored stop.*

Step back into the maximum workspace to start the guiding.



*For more information on the Pilot, refer to Chapter 5.1 the Arm in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).*

## 5.12 Guiding

### ⚠ CAUTION

#### Unexpected movement of Arm

Incorrect set mass and center of gravity values may lead to injuries, such as crushing.

- Check the mass and center of gravity for any end effector and the objects grasped by it.
- Correct the values if necessary.

#### Procedure

1. Press the Guiding Button and half-press the Enabling Button.

Guiding is now enabled.

*The status indicator on the base of the robot turns white.*

2. Guide the Arm by hand.
3. Stop the Hand-Guiding of the Arm.
4. Release the keys when the correct pose is reached.
5. Confirm the Pose by pressing the Teach Button.

Teaching a pose in the app is now completed.




Figure 23: Hand guide approval

### NOTICE

Do not use the external Enabling Button to guide the robot as it will lead to an error.

**NOTICE**

Do not guide the Arm when locked.

**NOTICE**

The vibration transmitted during hand-guiding is below  $2.5 \text{ m/s}^2$ . It was tested according to the test methods defined in DIN EN 1032:2009-02.

## 5.13 Editing end effector settings

A correct configuration is essential for operating Franka Research 3. When configuration is incorrectly, gravitational forces are not entirely compensated, and the Arm controls to the wrong target values.

### Procedure

1. Go to Franka UI.
2. Click on Settings.
3. Select the end effector sub-menu.

*The input mask opens.*

4. Enter the respective technical data, e.g., mass or mass inertia matrix.

In case of incorrect configuration, the following behavior might occur:

- The Arm may pull in certain directions in guiding mode.
- The control in operating mode may be affected so that the expected sensitivity of the Arm for collision detection is reduced.
- The tracking behavior may be affected.

As soon as the Task is taught and the correct end effector settings are set, switch to Test & Jog to test the Task at a reasonable execution speed. Make sure that there are no collisions and that everything works fine while being able to stop at any time by releasing the External Enabling Device.

### Initiating motion

An optional countdown for Task execution can be configured and edited in Settings.

When starting a Task in either Test & Jog or Work mode, the countdown is displayed before executing the Task. During the countdown, the LEDs on the robot base will indicate the started Task by fast-flashing in green.

**NOTICE**

After a system reboot, the control token is being reset.

**NOTICE**

Adjust the waiting time in the system settings. By default, the waiting time is set to 0 seconds.




Figure 24: Test & Jog

## Testing

### Precondition

- The robot has learned a Task.
- The External Enabling Device must be connected to X4.
- The operator must have left the maximum workspace.
- The operator must check that all other persons have left the safety zone.
- The operator must direct his full attention to the pending robotic motion.

### Procedure

To enable the robot, press the button on the External Enabling Device. Optional: Select an appropriate execution speed in the "Operation" section of the sidebar. *Default speed is 0.25m/s*

Press and hold the Test&Jog play button in the "Operation" section of the sidebar.

Task execution will be terminated if either the Play button or the External Enabling Device is released.

If a countdown for Task execution has been configured, a confirmation dialog is shown as well. During the countdown, the execution can still be cancelled. Robot lights are flashing green quickly during the countdown.

If the robot executes the task as intended, proceed to Task settings

If adjustments need to be made, go back to **Work**

**NOTICE**

The system monitors the connection of the Franka UI hold-to-run control with a maximum timeout of 1 s. If a connection loss is detected while a hold-to-run control is pressed, the system is stopped.

## 6 FRANKA UI

Franka UI is the user interface of the robots from Franka Robotics.

- It can be used to program and operate the robot in Desk.
- General settings can be made via Settings and the necessary safety adjustments are configured via Watchman.
- Franka UI is always reachable via the URL <https://robot.franka.de> if the user terminal is connected to X5 - robot network at the robot base and the DHCP client is activated.

### 6.1 Login

After entering the URL <https://robot.franka.de> the login to the user interface appears.




Figure 25: Franka UI

#### 6.1.1 Elements

1. Language selection
2. Network Status
3. Login

4. Watchman
5. Download Log-Files

1. ***Language selection***

Click to select the languages available for the user interface.

2. ***Network Status***

Display of the current IP address of the robot and the registered name of the robot in Franka World.

Clicking opens a menu with the following selection:

- Link to Franka World, with indication whether the robot is connected to Franka World (green or red dot).
- Shut Down Button, to shut down the robot.
- Manuals Button, clicking on it opens a download page of the Control with the possibility to open the user manual in all available languages.



Figure 26: Download User Manual

3. ***Login***

Input field for login; after a user log in, the view of DESK appears.

4. ***Watchman***

Direct access to the Watchman user interface in viewing mode.

5. ***Download Log***

Button for downloading the log files of the Robot.

## 6.2 Desk

### 6.2.1 Overview

Desk is the user interface in Franka UI for programming, configuring and operating the robot. To open Desk, enter the following URL in the browser: <https://robot.franka.de> and log in.

In Desk, you can create Tasks. Tasks are chronological sequences of Apps. Apps, in turn, are the building blocks of a Task and outline the basic abilities of Franka Research 3, e.g. "Grasp", "Put down" or "Press button".




Figure 27: Desk

## 6.2.2 Elements

1	Quick Navigation	5	Timeline
2	Language selection	6	Tasks
3	System Menu	7	Apps
4	User Menu	8	Sidebar

### 1 Quick Navigation

To switch quickly between the displays of Desk, Watchman and Settings.

### 2 Language Selection

Click to select the languages available for the user interface.

### 3 System Menu

Display of the current IP address of the robot and the registered name of the robot in Franka World.

Clicking opens the system menu with the following selection:

- [Link to Franka World](#); with indication whether the robot is connected to Franka World (green or red dot).
- [Reboot Button](#); to reboot the Robot.
- [Shut Down Button](#), to shut down the robot.
- [Activate FCI Button](#).
- [Manuals Button](#): Clicking on it opens a download page of the Control with the possibility to open the user manual in all available languages.

## 4 User Menu

The login information displays the currently logged in user and their role. Clicking this button opens the User menu with the following selection:

- [Release Control](#); Handing over control of the robot.
- [Log Out](#); Logout of the current user from the user interface.

## 5 Timeline

Arrange your apps in the timeline to program your task. The timeline represents the chronological sequence of a task.

## 6 Tasks

All configured tasks of the robot are listed in the "Tasks" area. Here you can access existing tasks and manage the tasks. You can also create, download, clone, rename, or delete tasks. Import a Task by dragging and dropping a Task file downloaded from the current or another robot into the Tasks area.

Tasks from an older generation of robot systems from Franka Robotics are not supported by Franka Research 3.

### NOTICE

Make sure you always back up system logs, security logs, and created tasks.

## 7 Apps

All installed apps from Franka World can be viewed here. The apps from this section of Desk can be used directly in the Tasks section. Drag and drop the desired apps into the timeline to use and configure them.

## 8 Sidebar

The sidebar allows the user to control the robot by selecting pilot mode (1), selecting a hand-guide mode (2), locking/unlocking the joints (3), or turning the end effector on and off (4). It displays the current status of the robot and important messages (5 & 6). It also allows changing the operating mode (7) and starting tasks (8) to execute or test them.

- 1 **Pilot Mode:**  
Switching between desk control and end effector control
- 2 **Guiding Mode:**
  - Translation
  - Rotation
  - Free
  - User defined
- 3 **Locking Joints:**
  - Lock
  - Unlock
- 4 **Activate End Effector:**
  - Switch On
  - Switch Off
- 5 **Status indication Robot**  
Status and Messages
- 6 **Status bar**  
Colored display of the robot status, see color table in Chapter 11.1 "Switching On"
- 7 **Operation mode**
  - Programming
  - Execution
- 8 **Start Execution**




Figure 28: Desk Sidebar

## 6.3 Watchman

With the Watchman web application, only a "Safety Operator" user can edit, validate, and integrate safety settings. However, any user is authorized to view the current safety settings in Watchman.

To view the current safety settings in Watchman, click "WATCHMAN" in the top menu bar or go to <https://robot.franka.de/watchman> in the browser.




Figure 29: Watchman

The detailed description of the interface as well as the procedure for configuring the safety settings of the robot can be found in Chapter Safety Functions.

## 6.4 Settings Interface

Various functions for configuring the robot are available to administrators in the Settings interface.




Figure 30: Menu Settings

## 6.4.1 Elements

1	System Overview (Dashboard)	5	Modbus TCP
2	Network Settings	6	System
3	User Management	7	Franka World
4	End Effector	8	Safety

### 1 Dashboard (Overview of the system status)

- System information about the control
- System information about the Arm
- Network information of the connected networks

### 2 Management of network configurations

- Address configuration of the X5 robot network
- Configuration of the company network C2

### 3 User management

- Creating, editing and removing users

### 4 Configuration of the end effectors

- Activating the power supply of the end effector
- Selection of the end effector
- Configuration of the end effector parameters

### 5 Modbus Configuration

- Download Modbus Manual
- Activating the Modbus function
- Upload and download the Modbus configuration

### 6 System

- Downloading of System-logs
- Reset to factory settings
- Move to pack pose

### 7 Franka World Synchronisation

- Installation of Apps und Features
- Software-Updates with Franka World

### 8 Safety

- Downloading of Safety logs
- Configuration the delay for movement initiation
- Configuration of SPoC-Token-forced timeout

# 7 ROLES AND PERSONNEL

## 7.1 Personnel

### 7.1.1 Responsible person

The responsible person is responsible for compliance with occupational health regulations and the operational safety ordinance. The responsible person for Franka Research 3 can be in particular the entrepreneur, the director of the institute, the employer, or a delegate responsible for the use of Franka Research 3.

The responsible person is responsible for the following:

- The responsible person must fulfil the monitoring obligations.
- The responsible person must ensure that all staff members working with Franka Research 3 are suitably qualified to do so and have been informed about the possible dangers Franka Research 3 may present.
- The responsible person must provide training and instructions in given intervals to create and consolidate risk awareness.

### 7.1.2 User

Users of the system are the people who are directly involved in the operation of the system. The operation of the system is divided into different tasks that cover the different operating phases of the system:

- Administrative tasks
- Safety related tasks
- Operation of the system

According to the assigned tasks, users must have qualified knowledge of the subject area of the task, safety instructions and training on the robot system. The required qualifications are described below in the description of the user roles.

### 7.1.3 Integrator

The integrator is responsible for assembling the partly completed machinery into the final machinery by combining the robot with other equipment or another machine, including other robots, to form a machine system.

The integrator also conducts an appropriate risk assessment to identify residual risks and eliminate or minimize them.

The integrator is responsible for the safety of the final application.

***For more information, please refer to chapter 4 section 4.2 Notice of liability in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).***

#### NOTICE

Only qualified or sufficiently trained personnel that possess adequate technical skills are permitted to operate the robot. The qualification of said personnel includes but is not limited to professional technical education, a university degree in engineering, or professional experience in the field of robotics or automation.

Franka Robotics suggests a product specific training performed by Franka Robotics, partners, and affiliates.

## 7.2 User Roles

### 7.2.1 Operator

An operator can access Franka Research 3 and utilize Franka UI to use Franka Research 3 within the limits defined by the responsible person, the administrator, and the safety operator. The operator can utilize the user interface Franka UI as follows:

- Start, monitor, and stop the intended operation of Franka Research 3
- Download and select Tasks
- View Tasks and App settings
- View status of the system (network, robot, end effector)
- View safety settings
- Lock/unlock joints
- Start/stop a task
- Guiding (no saving of poses possible)
- Switchover Pilot-Mode
- Move to transport pose for packing
- Download log files from the system
- Shutdown and reboot the system

The operator only has limited access to Franka UI.

### 7.2.2 Administrator

The administrator has all the rights that the operator has. An administrator is a person authorized by the responsible person to set up and access the robotic system and to utilize the user interface Franka UI as follows:

- User management (create, update and delete users; assign roles and modify passwords)
- Set and change non-safety-related parameters of the system (e.g., change end effector settings)
- Program and teach the robot system
- Install system updates, features, and apps
- Edit system configuration
- Create, edit, and set parameters for tasks

### 7.2.3 Safety operator

The safety operator has the same rights as the operator, plus the rights to set up and validate safety settings. The safety operator can utilize Franka UI as follows:

- Edit safety configurations
- Program and teach the robot system
- Create, edit, and set parameters for tasks
- Recovering of specific Safety errors

**NOTICE**

User roles should only be assumed by qualified or sufficiently trained personnel. They should be instructed on the conduct in emergency or abnormal situations. The Responsible Person must choose the personnel based on experience, training, or similar existing duties in robotics, automation, Industrial safety and occupational health.

## 7.2.4 Assigning user roles

### 7.2.4.1 *Assign an administrator*

When logging in for the first time, creating an administrator user is compulsory.

1. Enter a username.
2. Enter a password.
3. Confirm the password.

Administrator login information should be kept safely and securely. The only way to access the role as administrator without a password is to perform a factory reset that deletes all prior information.

**NOTICE**

Always use secure passwords to prevent unauthorized persons from accessing the system.

### 7.2.4.1 *Creating and editing users*

There must always be at least one user with the Administrator role defined. This means that the last administrator cannot be deleted. Every user must be assigned a role, and several users can have the same role. Franka Research 3 supports the roles described above.

#### Procedure

1. Log into the Franka UI. For information on Franka UI, see chapter FRANKA UI.
2. Go to Settings.
3. Click on the Users tab.
4. Add new users or edit existing ones.

# 8 MANAGING FRANKA RESEARCH 3

## 8.1 Managing Apps and Updates

Apps and features purchased through the Franka World Store can be accessed and installed on the robot via the "Franka World" tab in the Settings interface. When the robot is online, synchronization between the robot and the Franka World account is simple and fast. However, the operator can also perform the synchronization manually on the same interface, should the robot be offline. Depending on whether the robot is online or offline, the view adjusts automatically.




Figure 31: Managing Apps and Features via Franka World

### NOTICE

If required, the operating system will update when new Apps or features need to be installed from Franka World.

## Registering of Robot

### Precondition

- The robot must be online.
- You must be logged in to Franka World.




Fig. 8.32: Network connection of control

#### Procedure

1. Navigate to Settings.
2. Click on REGISTER DEVICE.

*You will be redirected to a different site that states your robot's serial number and other proof of ownership.*

3. If required, enter your e-mail and password and log in.

*You will be redirected to another site.*

4. Choose an account for registering your robot.
5. Click REGISTER.

*The robot is now registered.*

6. Navigate to Manage.
7. To see all registered robots, click on Devices.

## 8.2 Hub

Hub is the central knowledge section within Franka World. It provides access to documentation, tutorials, codes, and updates about our robot of Franka Robotics and its interfaces. Find more information on <https://franka.world/>.

## 8.3 Updates

### System updates

Updates for the operating system can be downloaded conveniently via the "Franka World" tab in the Settings view. To do this, the robot must have online access to Franka World.

The Control regularly checks for available updates to the operating system and displays them in the "Franka World" tab of the Settings interface.




Figure 33: Managing of Updates via Franka World

If you want to apply the updates, click on "DOWNLOAD". The update data will be downloaded. After the download is complete, the "Apply changes" display is highlighted. Now click on "NEXT" to perform the installation.

After the update, the operating system will be restarted. The power supply to the robot must not be interrupted during this time.

If your robot does not have online access to Franka World, you can also start an update manually. For this purpose, the update file can be downloaded from the Franka World page and uploaded to the robot via the operating device connected to the robot. To do this, click on "UPLOAD" in the "Franka World" tab of the Settings interface and select the previously downloaded download file. After manually uploading the update file to the robot, confirmation is required to install, analogous to the online procedure.

After the manual installation of the update, a download button for the status file of the performed update will appear. Download the file and upload it again to your Franka World account. This status file synchronizes the update status of your robot with Franka World.

### NOTICE

If required, the operating system will update when new Apps or features need to be installed from Franka World.

## 8.4 Backup

A Backup of the Control consists of several relevant categories of Control data. These are usually:

- Safety Configuration of the system,
- Network Settings,
- ModBus-Configuration,
- End effector configuration,

- User configuration,
- created Tasks.

With the actual available firmware or previous versions of the Control, a system backup must be performed manually in five individual steps. These steps are:

- ✓ Saving of the Safety Configuration
- ✓ Saving of the network Settings
- ✓ Saving of the ModBus-configuration
- ✓ Saving of the End effector configuration
- ✓ Saving of the created Tasks

A backup of the User administration is currently not possible. We recommend saving the created users and their configured authorization as a screenshot and saving it as a file with the remaining backup data. With the current firmware, a restoring of the user administration can only be done by recreating the users.

Create a backup directory for the backup files on a suitable storage medium connected to your user interface device. The steps required to create the backup data are explained below.

## 8.5 Safety Configuration

The safety configuration cannot be saved as a backup file in the current firmware. To perform a backup of the created configuration, the report must be opened in Watchman and saved as a PDF in the backup directory. To do this, proceed according to the following steps:

- ✓ Select Watchman in the Desk menu
- ✓ Click on „Report“ in the upper left corner of the Watchman user interface.
- ✓ Save the report as a PDF and place it in the backup directory.

There are two more parameters of the security configuration to be saved outside of the Watchman interface. To do this, proceed as follows:

- ✓ Select „Settings“ in the DESK menu
- ✓ Open the „Safety“ tab.
- ✓ Take a screenshot of this view and save it in the backup directory.

The relevant parameters in this section are:

- Work Execution Wait Time
- Token Force Timeout

In case of a recovery, the parameters and rules must be entered and validated manually in Watchman or in the „Settings/Safety“ tab.

## 8.6 Network Setting

To save the network settings, proceed with the steps below:

- ✓ Open the „Settings“ on Desk
- ✓ Select „NETWORK“ tab
- ✓ Take a screenshot of this view and save it in the created backup directory.




Figure 34: Network Settings

In case of necessary configuration recovery, the parameters listed in the screenshot must be entered manually.

## 8.7 Modbus Configuration

To save the Modbus configuration, proceed with the steps below:

- ✓ Open the „Settings“ on Desk
- ✓ Select the „MODBUS TCP“ tab
- ✓ Clicking on „DOWNLOAD“ saves the Modbus configuration with the following name on the connected user interface device: „modbus.json“

Save the downloaded file in the previously created backup directory.

Via the "UPLOAD" button you can restore a backup file of the Modbus configuration to the system again.

## 8.8 End Effector Configuration

To save the end effector configuration, proceed with the steps below:

- ✓ Open the „Settings“ on Desk
- ✓ Select the „END\_EFFECTOR“ tab
- ✓ Click on the edit symbol next to „Mechanical Data“
- ✓ Clicking on „DOWNLOAD“ saves the Modbus configuration with the following name on the connected user interface device: „endeffector-config.json“

Save the downloaded file in the previously created backup directory.

Via the "UPLOAD" button you can restore a backup file of the End effector configuration to the system again.

## 8.9 Saving of the created Tasks

The created Tasks can be downloaded individually in the „DESK“-View.

To download a Task, proceed with the steps below:

- ✓ Open the „Settings“ on Desk
- ✓ Select the desired Tasks
- ✓ Clicking on the download symbol starts the download process.

Save all downloaded Tasks to the backup directory.




Figure 35: Save Tasks

To Restore a Task, move the downloaded task-file from file directory by dragging and dropping to the Task-List in DESK.

## 8.10 Franka World



Franka World is an online platform that interconnects customers, partners, and software and hardware developers, whose activity revolves around Franka Robotics's products and services. Franka World provides tools for managing Franka Research 3, access to an online store that features a continuously growing portfolio of software and hardware products, and the possibility of becoming part of an active and passionate community.

Visit <https://franka.world/> to make use of all the benefits.



Access the Franka World User Manual to get an overview of all Franka World features and how to benefit from them: <https://download.franka.de/franka-world-manual/>

# 9 TROUBLESHOOTING

## 9.1 General use

### 9.1.1 Recoverable errors

For a list of recoverable safety errors, see

Error	Solution
Franka Research 3 indicator is lit white	Possibly one of the two buttons on the Pilot-Grip has not been pressed properly. Release both buttons and half-press the Enabling Button while simultaneously pressing the Guiding Button again. Make sure that you do not completely press down the Enabling Button, otherwise the Arm's motion is stopped.
Franka Research 3 indicator changes to color pink	The system is receiving conflicting enabling signals. Close all inputs before moving the robot again. The opened inputs X3.1 (emergency stop) and X4 (External Enabling Device) are highlighted in pink in Desk.
Franka Research 3 indicator is lit or flashes yellow	The system has identified a warning in the system. The system might work with the active warning or not, depending on the type of warning.
Franka Research 3 indicator flashes red	An application error or safety violation has occurred. The error or violation must be fixed before the system fail-safe locking system can be released again from Desk.
Franka Research 3 indicator is lit red	There is a problem. If this cannot be rectified by restarting the system, please contact a contact partner, a service provider or us directly at: support@franka.de.

### 9.1.2 Arm pulls strongly in one direction during teaching

Immediately check the settings for the end effector and make sure that the correct end effector has been selected and configured. Make sure Franka Research 3 is mounted on a plain surface within the permitted tilt tolerance.

If you connect to a third party or custom-made end effector, ensure that you have compensated it correctly by updating the transformation matrix. To set the correct tool center point, adjust the weight, set the center of mass relative to the flange.

#### NOTICE

If a third party or custom-made end effector has been installed, check the following:

1. Update the transformation matrix to set the correct tool center point.
2. Adjust the weight of the end effector.
3. Set the center of mass relative to the flange.
4. Update the inertia matrix.

If the problem persists, please contact your service partner or customer support at support@franka.de. Do not operate the system until the issue is solved.

In the case of heavy external cabling, a drift cannot be prevented as that cannot be compensated with Franka Research 3 settings for all poses.

### 9.1.3 Loud clicking at switch-off

The clicking results from the deployment of the fail-safe locking system and is normal. Locking pins are deployed in the joints to lock them mechanically.

### 9.1.4 Joint limit error

In the event of a joint limit error, the joint of the robot was moved out of the permissible movement range. The following error message appears:




Figure 36: Message "A joint limit has been violated"

This error can only be corrected by a safety operator. The "START RECOVERY" button appears for logged-in safety operators.

Clicking on "START RECOVERY" starts the procedure for restoring the joint error. A dialog opens with the display of the affected joint.




Figure 37: Message with display of the faulty joint

Now activate the External Enabling Device and click on "Move Joint Out Of Limit". Hold both until the following message appears:




Figure 38: Confirmation joint is back in the limit

The joint is now inside the movement limit again. Now click on "CONFIRM" and thereby complete the recovery.

### 9.1.5 Joint position error

In the presence of a joint position error, the position data of a joint has been lost in the control system. This can be caused, for example, by a power failure with the brakes open. To rectify this error, a procedure is required that enables the position assignment or joint calibration to be restored. This error is indicated by the following message in Desk.




Figure 39: Message "Joint position error detected"

This error can only be corrected by a safety operator. The "START RECOVERY" button appears for logged-in safety users.

After clicking on "START RECOVERY", a message is opened in which the failed joints are displayed.




Figure 40: Message with display of failed joints

Click on any joint that has been reported failed. The view for restoring the joint is displayed.




Figure 41: Joint recovery locked

Now activate the External Enabling Device and keep it pressed until the recovery of the joint is completed. Click on the unlock icon of the joint.

**NOTICE**

When operating the External Enabling Device, make sure that you are outside the hazardous area to check the execution of the recovery from a safe distance.

Now, the Robot is unlocking this joint.




Figure 42: Joint recovery ready for movement

Then click on the "Move Joint To Ref. Position" button and keep it pressed until the reference position is reached on the robot. Alternatively, the "+" / "-" keys can also be used to move the robot.

When the joint has reached the correct position, the following message appears:




Figure 43: Conformation position reached

Visually check whether the affected joint has moved to the reference position. If this is not the case, i.e. a joint has not moved to the correct reference position, contact Support.

When the joint position is in the reference position, you can release the external enabling device again. Now check the box to confirm the correct reference position of the joint and click on the "CONFIRM" button. Now, the joint position is referenced again.




Figure 44: Confirmed Joint recovery

Now carry out the procedure described for all other joints that are still indicated as failed.

If you do not hold the buttons to move, the following message appears:




Figure 45: Message Button not held

If you end the procedure before reaching the reference position, the following message appears:




Figure 46: Message if reference position not reached

If you are unable to move to a joint position because it cannot be reached due to an interfering contour, you can move other joints of the robot first as required using the "+/-" keys and thus enable the reference positions of the joint to be referenced to be reached.

When all incorrectly reported joints have been referenced, the restoration of the robot's reference position is complete. Confirm the recovery by clicking "CONFIRM".




Figure 47: Confirm the complete recovery

The robot can now be used again.

**NOTICE**

After restoring joint position errors, the system cannot guarantee that previously taught poses are still approached correctly. Therefore, check the poses of your tasks before you start them in Execute.

If the recovery cannot be completed successfully, the robot hardware may have been damaged or there is a software error. In this case, shut down the system, take the robot out of operation and contact support.

### 9.1.6 Failed to unlock joints

If the joint unlocking process fails, follow the following steps:

1. Shut down the robot, unplug it from its power source, and remove the connecting cable between the Arm and Control. For information on how to safely shut down Franka Research 3, *see section **Disconnecting Franka Research 3 from the power** chapter 8 “switching off and restarting” in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).*
2. Check the pins for potential damage.  
If no damage can be observed, carefully but firmly reattach the cable and make sure it sits tight. Power up the robot and try to unlock the joints.
3. If the issue should persist, contact your service partner or customer support at support@franka.de by providing the serial number of the Arm and the log files of the robot. You can find the log files in Desk – Settings – System – Download log files.

### 9.1.7 Robot does not finish booting

#### Procedure

1. Turn off the Control.
2. Unplug the system from its power source.

For information on how to safely shut down Franka Research 3, *please refer to chapter 8.3 Switching off and restarting section ‘Disconnecting Franka Research 3 from the power supply’ in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).*

3. Remove the connecting cable between the Arm and Control.
4. Check the pins for potential damage.
5. If no damage can be observed, carefully but firmly reattach the cable and make sure it sits tight.
6. Power up the robot.

If the issue persists, contact your service partner or support@franka.de by providing the serial number of the Arm.

### 9.1.8 Desk continuously displays “Shutting down the system”

You have shut down the system. As soon as the front fans of the Control have stopped turning, the Control can be turned off using the switch on the rear side. Then the browser window of Desk can be closed.

### 9.1.9 Robot does not boot after turning on the Control

Occurs when the system has been turned off via Desk, but the Control power button was not turned off. Solution: Turn off the Control and wait for 1-2 minutes. Turn on again. Control should now boot.

### 9.1.10 Restarting after an unexpected stop

For restarting after an unexpected stop, refer to chapter 8.3 "Switching off and Restarting" in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).

## 9.2 Troubleshooting while using FCI

For errors related to the use of FCI, please refer to the online FCI documentation at <https://franka.world/>.

There you will find detailed and updated information on how to fix various error scenarios that may occur.

# 10 ADVANCE CONTROL

## 10.1 Franka Control Interface (FCI)

The Franka Control Interface (FCI) allows a fast and direct low-level bidirectional connection to the Arm, Franka Hand and Cobot Pump. It provides the current status of the robot and enables its direct control with an external workstation PC connected via Ethernet.




Figure 48: Schematic overview FCI

Using libfranka, our open source C++ FCI client, you can send real-time control values at 1 kHz with 5 different interfaces:

- Gravity & friction compensated joint level torque commands.
- Joint position commands
- Joint velocity commands.
- Cartesian pose commands.
- Cartesian velocity commands.

At the same time, you get access to 1 kHz measurements of:

- Measured joint data, such as the position, velocity and link side torque sensor signals.

- Estimation of externally applied torques and forces.
- Various collision and contact information.

You also get access to the robot model library which provides:

- Forward kinematics of all robot joints.
- Jacobian matrix of all robot joints.
- Dynamics: inertia matrix, Coriolis and centrifugal vector and gravity vector.

In addition, `franka_ros` and `franka_ros2` connects Research robots of Franka Robotics with the entire ROS and ROS2 ecosystem. It integrates `libfranka` into [ROS Control](#). Additionally, it includes [URDF](#) models and detailed 3D meshes of our robots and end effectors, which allows visualization (e.g. RViz) and kinematic simulations. [MoveIt! / MoveIt!2](#) integration makes it easy to move the robot and control the gripper, and the provided examples in [MoveIt! / MoveIt!2](#) show you how to control your robot using ROS.

 **WARNING**

NOTICE that control of the robot via FCI is not possible when the SLP-C, SLS-C or SLP-J functions are active. This affects the safety functions that include spatial position monitoring (Inside/Outside Area) and Cartesian velocity monitoring (maximum speed). If these are used in rules in Watchman, control via FCI is not possible.

**NOTICE**

Data is sent over the network with a frequency of 1 kHz. Therefore, a good network connection is required!

**NOTICE**

While the FCI is active you have full, exclusive control of the Arm and Franka Hand. This means that Arm control cannot be performed via Apps and FCI at the same time!

## 10.2 Working in principle with the FCI interface

Controlling the robot via the FCI interface can be realized by using `libfranka` in the C++ environment. A sound knowledge of Linux environment and C++ programming is recommended for this purpose. Alternatively, the robot can be controlled via the FCI interface by ROS, ROS 2.

The following section describes the basic procedure for programming with the help of `libfranka` in the C++ environment.

### Executables

Via the `libfranka` described before in chapter 8.1. executable files (executables) can be created.

In the "examples" subfolder of `libfranka`, examples of executables are listed. You can use these as a base to get started easily and create copies from them that are customized according to your requirements.

Below you will find the source code of the example " *generate\_joint\_position\_motion.cpp* " from libfranka to explain the structure of a script.

```
// Copyright (c) 2017 Franka Robotics GmbH
// Use of this source code is governed by the Apache-2.0 license, see LICENSE

#include <cmath>
#include <iostream>

#include <franka/exception.h>
#include <franka/robot.h>
#include "examples_common.h"

/***
 * @example generate_joint_position_motion.cpp
 * An example showing how to generate a joint position motion.
 *
 * @warning Before executing this example, make sure there is enough space in front of the robot.
 */

int main(int argc, char** argv) {
    if (argc != 2) {
        std::cerr << "Usage: " << argv[0] << " <robot-hostname>" << std::endl;
        return -1;
    }
    try {
        franka::Robot robot(argv[1]);
        setDefaultBehavior(robot);

        // First move the robot to a suitable joint configuration
        std::array<double, 7> q_goal = {{0, -M_PI_4, 0, -3 * M_PI_4, 0, M_PI_2, M_PI_4}};
        MotionGenerator motion_generator(0.5, q_goal);
        std::cout << "WARNING: This example will move the robot!
        << "Please make sure to have the user stop button at hand!" << std::endl
        << "Press Enter to continue..." << std::endl;
        std::cin.ignore();
        robot.control(motion_generator);
        std::cout << "Finished moving to initial joint configuration." << std::endl;
        // Set additional parameters always before the control loop, NEVER in the control loop!
        // Set collision behavior.
        robot.setCollisionBehavior(
            {{20.0, 20.0, 18.0, 18.0, 16.0, 14.0, 12.0}}, {{20.0, 20.0, 18.0, 18.0, 16.0, 14.0, 12.0}},
            {{20.0, 20.0, 18.0, 18.0, 16.0, 14.0, 12.0}}, {{20.0, 20.0, 18.0, 18.0, 16.0, 14.0, 12.0}},
            {{20.0, 20.0, 20.0, 25.0, 25.0}}, {{20.0, 20.0, 20.0, 25.0, 25.0}},
            {{20.0, 20.0, 20.0, 25.0, 25.0}}, {{20.0, 20.0, 20.0, 25.0, 25.0}});
        std::array<double, 7> initial_position;
        double time = 0.0;
        robot.control(&initial_position, &time)(const franka::RobotState& robot_state,
            franka::Duration period) -> franka::JointPositions {
            time += period.toSec();
            if (time == 0.0) {
                initial_position = robot_state.q_d;
            }
        }
    }
}
```

```

double delta_angle = M_PI / 8.0 * (1 - std::cos(M_PI / 2.5 * time));

franka::JointPositions output = {{initial_position[0], initial_position[1],
                                 initial_position[2], initial_position[3] + delta_angle,
                                 initial_position[4] + delta_angle, initial_position[5],
                                 initial_position[6] + delta_angle}};

if (time >= 5.0) {
    std::cout << std::endl << "Finished motion, shutting down example" << std::endl;
    return franka::MotionFinished(output);
}

return output;
};

} catch (const franka::Exception& e) {
    std::cout << e.what() << std::endl;
    return -1;
}

return 0;
}

```

In C++ texts are excluded via the character string "///". These serve e.g. as information of the programmer to the program structure.

The include command "#include <path-spec>" at the beginning of the script instructs the processor to include the content from the in the path specification at the point where the -statement is displayed. For example, you can use this to access predefined functions from libfranka.

The line "int main(int argc, char\*\* argv) { }" contains the command line parameters inside the single brackets. Inside the curly braces is the actual main function of the script. The main function is terminated by a closing curly bracket.

In the main function, various commands can now be executed or calls to included sub-functions can be made.

As mentioned before, the control of the robot requires a profound knowledge of C++ programming.

#### NOTICE

To intercept the immediate start of the robot's movement, Franka Robotics recommends to create a query procedure at the beginning of a script, which will execute the program only after active confirmation. Such queries can also be found in the sample scripts in libfranka.

## Creating or modifying executables

If you want to create your own executables, we recommend that you create your own project. To do this, create your project folder. In this folder you have to create a "CMakeLists.txt". This file should be structured according to the following scheme.

```

project(hello_world)
find_package(Franka REQUIRED)

```

```
add_executable(hello_world hello_world.cpp)
target_link_libraries(hello_world Franka::Franka)
```

Store your source code files for your executables (xxxxx.cpp) in your project folder. Add your source codes to the "CMakeLists.txt" file accordingly.

Now create a build folder in your project. And from this folder, run the following command:

```
cmake ..
```

Your build will now be created according to the CMakeLists.txt.

Then, to compile, run the following command from your build folder:

```
make
```

Your project is now successfully compiled.

## Execution of Executables

To run executables, you must run them from the build you created for your project.

An executable is executed by opening a terminal in the build folder of your project where it is stored and executing the following command:

```
./name executable <ip robot>
```

Enter the name of the executable and the IP address of the robot.

The script will now be executed.

### ⚠️ WARNING

The execution of an executable can directly initiate movements of the robot and thus lead to injuries.

Before starting an executable, make sure that there are no people in the danger zone of the robot!

To stop / cancel the execution of an executable, you can press the key combination <CTRL>+<C>.

## 10.3 Setup of Franka Control Interface (FCI)

To operate the robot via the Franka Control Interface (FCI), the FCI-Feature must be installed on your device. If it is already installed on the controller, it will be listed under Franka UI -> Settings -> System -> Installed Features. By default, the FCI feature is automatically installed during initial configuration. If FCI is not already installed, you can install it on Control with your Franka World account.

To control the robot via the Franka Control Interface (FCI), the operating device must be connected to the C2 – Shop floor network port on controller via an Ethernet cable.

### NOTICE

Control via FCI is only possible via the C2 – Shop floor network port. The use of the X5 - Robot network port on the robot foot is not suitable for the use of the FCI function.




Figure 49: Network connection for FCI Usage

### 10.3.1 Network Configuration for FCI

Good network performance is critical for controlling the robot via the FCI interface. It is therefore strongly recommended to use a direct connection between the workstation PC and Control. This section describes how to configure your network for this use case.

To operate and control the robot via the FCI interface, an external operating device in the form of a PC or laptop with a Linux operating system (e.g. Ubuntu) is recommended.

Hardware recommendation:

- Commercially available PC, laptop with Linux
- Ethernet interface
- Resolution min. 1280x720px, recommended Full HD (1920x1080 px)
- Recommended browsers: Chrome or Firefox

### 10.3.2 Static IP Configuration Example

Control and your workstation must be configured to appear on the same network. The simplest way to achieve that is to use static IP addresses. Any two addresses on the same network would work, but the following values will be used for the purpose of this example:

	Workstation PC	Control
Address	172.16.0.1	172.16.0.2
Netmask	24	24

The Control's address (172.16.0.2) is called <fci-ip> in the following chapters.

#### NOTICE

With this network configuration, Franka UI can be accessed via <https://<fci-ip>>, although you will see a certificate warning in your browser.

### 10.3.3 Configuring Control's Network

1. Connect to the **X5 – Robot network port** on the robot base.
2. Open **Administrator Settings** in Franka UI.
3. Navigate to **C2 – Shop Floor network** settings.
4. Deactivate **DHCP Client**.
5. Enter static IP settings for LAN connection.
6. Press **Apply** to confirm.




Figure 50: Network settings

### 10.3.4 Configuring the Operating Device (Ubuntu 20.04)

This section describes how to set up a static IP address on Ubuntu 20.04 using GUI. Follow the official Ubuntu [guide](#) if you prefer to use the command line.

These steps modify your network settings. Contact your network administrator if you are unsure.

**Steps:**

1. Open the **Network Connection** widget.
2. Select the wired connection and click **Edit**.
3. Go to the **IPv4 Settings** tab.
4. Set the method to **Manual**.
5. Enter the following values:




Figure 51: Values

6. Save changes and close the window.
7. Select the connection from the drop-down menu to activate it.




Figure 52: Ubuntu – setting a static IP

### NOTICE

This step will disable DHCP, which means you will no longer obtain an address when connecting to a DHCP server, like the one in Arm's base (X5 – Robot network). When you no longer use FCI, you can change the method back to *Automatic (DHCP)*.

#### Final Steps

After configuration, you can access Franka UI via <https://<fc1-ip>> in your browser.

To verify network quality, perform a communication test for bandwidth, delay, and jitter.

## 10.4 Setup of libfranka on a Linux workstation

Recommended for the setup is an Ubuntu 22.04 Pro version or newer. In this version, Ubuntu already provides the required RT kernel, but it may be chargeable depending on the usage.

If you are using an Ubuntu version without a provided RT kernel, it must be installed before libfranka is patched. The real-time kernel is used to realize the real-time transmission with 1 kHz of the signals between Control and the operating device.

The setup of libfranka then requires two steps, which must be performed one after the other. For the execution you need full "admin" rights on your Linux PC.

Further information can also be found in [FCI-Documentation via Franka World](#).

## Installation PREEMPT\_RT Kernel

In the first step, if an RT kernel has not yet been installed with the Ubuntu version, a PREEMPT Real-Time kernel must be installed. To do this, create a new folder in your Linux PC's drive and start the terminal from it.

### NOTICE

NVIDIA binary drivers are not supported on PREEMPT\_RT-kernels.

To install, proceed now according to the following steps:

### NOTICE

To avoid typing errors when entering commands, open the online FCI documentation and copy the command lines there, which you can then paste and execute in the terminal.

- **Download**

To install the dependencies, enter the following command in the Terminal:

```
sudo apt-get install build-essential bc curl ca-certificates gnupg2 libssl-dev lsb-release libelf-dev bison flex dwarves zstd libncurses-dev
```

Then you need to decide which kernel version you want to use. Use the following command to find out which version you are currently using.

```
uname -r
```

Real-time patches are only available for select kernel versions, see <https://www.kernel.org/pub/linux/kernel/projects/rt/>. We recommend choosing the version closest to the one you currently use.

The version tested by Franka Robotics is the 5.9.1 for Ubuntu 20.04, on which the following installation steps are based.

Use the command lines below to download the source files.

If you have chosen a different version, change the version number (5.9.1) in the command lines to match the version you have chosen.

```
curl -SLO https://www.kernel.org/pub/linux/kernel/v5.x/linux-5.9.1.tar.xz
curl -SLO https://www.kernel.org/pub/linux/kernel/v5.x/linux-5.9.1.tar.sign
curl -SLO https://www.kernel.org/pub/linux/kernel/projects/rt/5.9/patch-5.9.1-rt20.patch.xz
curl -SLO https://www.kernel.org/pub/linux/kernel/projects/rt/5.9/patch-5.9.1-rt20.patch.sign
```

Then decompress the downloaded data with the command:

```
xz -d *.xz
```

- **Verification**

After downloading the dependencies, it is recommended that you check them to see if they have been corrupted or tampered with. The steps recommended for this are taken from the [Linux Kernel Archive](#).

Use the following commands to check:

```
gpg2 --verify linux-*.tar.sign
gpg2 --verify patch-*.patch.sign
```

If all loaded packages are correct, you will receive a message corresponding to the following example for each command.

```
$ gpg2 --verify linux-*.tar.sign
gpg: assuming signed data in 'linux-4.14.12.tar'
gpg: Signature made Fr 05 Jan 2018 06:49:11 PST using RSA key ID 6092693E
gpg: Good signature from "Greg Kroah-Hartman <gregkh@linuxfoundation.org>" [unknown]
gpg:           aka "Greg Kroah-Hartman <gregkh@kernel.org>" [unknown]
gpg:           aka "Greg Kroah-Hartman (Linux kernel stable release signing key) <greg@kroah.com>" [unknown]
gpg: WARNING: This key is not certified with a trusted signature!
gpg:           There is no indication that the signature belongs to the owner.
Primary key fingerprint: 647F 2865 4894 E3BD 4571 99BE 38DB BDC8 6092 693E
```

See [Linux Kernel Archive](#) for more information about the warning.

If the check returns an error, then you will receive a message corresponding to the example below.

```
$ gpg2 --verify linux-*.tar.sign
gpg: assuming signed data in 'linux-4.14.12.tar'
gpg: Signature made Fr 05 Jan 2018 06:49:11 PST using RSA key ID 6092693E
gpg: Can't check signature: No public key
```

In this case, you must download the key from the key server.

To do this, use the following command for both "\*.tar" and "\*.patch" and enter the ID specified in the respective error message in the command line.

```
gpg2 --keyserver hkp://keyserver.ubuntu.com:80 --recv-keys 6092693E
```

- **Compiling the kernel**

Once you are sure the files were downloaded properly, you can extract the source code and apply the patch. To do this, enter the following commands one after the other:

```
tar xf linux-*.tar
cd linux-*/
patch -p1 < ../patch-*.patch
```

Get the current name of the patch with the command:

```
uname -r
```

Als nächstes kopieren Sie mit der nachfolgenden Befehlszeile Ihre aktuell gebootete Kernelkonfiguration als Standardkonfiguration für den neuen Real-Time-Kernel. Über „uname -r“ wird automatisch der aktuelle Kernel ausgewählt.

```
cp -v /boot/config-$(uname -r) .config
```

Now you can use this configuration as the default for configuring the build. To do this, enter the following commands:

```
make olddefconfig
make menuconfig
```

The second command opens a terminal interface (TUI) where you can configure the preemption model.




Figure 53: TUI-Interface

- Navigate with the up/down keys to "General Setup" > "Preemption Model" and mark there > "Fully Preemptible Kernel (Real-Time)" By using the side arrow keys you can move the cursor to Select in the command line at the bottom of the screen. Now press <Enter> and the selection is chosen.
- Set the cursor in the command line to <EXIT> and press <Enter> repeatedly until you return to the main menu.
- Now navigate to "Cryptographic API" > "Certificates for signature checking" (at the very bottom of the list) > "Provide system-wide ring of trusted keys".
- There, select "Additional X.509 keys for default system keyring" and press Enter. An input window opens. Remove the entry "debian/canonical-certs.pem" from the prompt and press Ok.
- Now navigate to "Cryptographic API" > "Certificates for signature checking" (at the very bottom of the list) > "Provide system-wide ring of revocation certificates".
- There select "X.509 Certificates to be preloaded into the system blacklist keyring" and press Enter. An input window opens. There remove the entry "debian/canonical-revoked-certs.pem" from the prompt and press Ok.
- Save this now the configuration in .config and exit the terminal interface (TUI).

Now the installation is ready for the kernel to be compiled. Since this is a lengthy process, the "nproc" command automatically uses the multithreading option "-j" on the command line to use the maximum number of cores on your CPU. Nevertheless, this step takes longer time.

```
make -j$(nproc) deb-pkg
```

Now you can install the newly created package with the following command. The exact names depend on your environment. The command searches for the header and images packages.

```
sudo dpkg -i ../linux-headers-*.deb ../linux-image-*.deb
```

- **Verifying the new kernel**

Restart your system. The grub boot menu should now allow you to choose your newly installed kernel. To see which kernel will be used after the boot, look at the output of the following command:

```
uname -a
```

It should contain the string PREEMPT\_RT and the version number you chose. Additionally, /sys/kernel realtime should exist and contain the number „1“.

#### NOTICE

- If you encounter errors that you fail to boot the new kernel see „[Cannot boot realtime kernel because of Invalid Signature](#)“.
- If you want to re-do the build, then delete all the unzipped data from your installation folder beforehand.

- **Allow a user to set real-time permissions for this process**

After the PREEMPT\_RT-Kernel is installed and running, add a group named *realtime* and add the user controlling your robot to this group.

You can get your user name from the command line:

```
whoami
```

```
sudo addgroup realtime
sudo usermod -a -G realtime $(whoami)
```

Then open the "limits.conf" file with the following command:

```
sudo gedit /etc/security/limits.conf
```

Then add the following real-time group limits to the file and save them.

```
@realtime soft rtprio 99
@realtime soft priority 99
@realtime soft memlock 102400
@realtime hard rtprio 99
@realtime hard priority 99
@realtime hard memlock 102400
```

The limits will be applied after you log out and in again.

#### Installation Libfranka

The next step describes how to install libfranka from source files. Alternatively, libfranka can be installed by ROS-repos (<Ubuntu 22.04) or ROS2-repos (Ubuntu 22.04 and later).

You can also find further assistance in the [FCI-Dokumentation](#) on [Franka World](#).

#### NOTICE

To avoid typing errors when entering commands, open the online FCI documentation and copy the command lines there, which you can then paste and execute in the terminal.

Before building the new libfranka from source, please uninstall existing installations of libfranka and franka\_ros to avoid conflicts.

To do this, run the following command in the terminal:

```
sudo apt remove "libfranka"
```

- **Download**

To install libfranka, the dependencies must be downloaded. To do this, enter the following command line:

```
sudo apt install build-essential cmake git libpoco-dev libeigen3-dev
```

Then download the source code by cloning libfranka from GitHub and then change to the directory. To do this, use the following commands:

```
git clone --recursive https://github.com/frankarobotics/libfranka --branch 0.10.0
cd libfranka
```

- **Install**

Then, the following commands create a build folder in the current directory and run the "CMake" command to create the build / project files.

```
mkdir build
cd build
cmake -DCMAKE_BUILD_TYPE=Release -DBUILD_TESTS=OFF ..
cmake --build .
```

It is recommended to install the optional libfranka Debian package. To do this, enter the following command in the same directory that creates the "libfranka-<version>-<architecture>.deb" package.

```
cpack -G DEB
```

This is then installed by the following command.

```
sudo dpkg -i libfranka*.deb
```

The libfranka is now installed on your PC and can be used to control the robot via FCI.

## 10.5 Verification of communication

After the successful compilation / installation of libfranka, a test of the communication of the interface is recommended. To do this, make sure that the robot is prepared for FCI use in Desk and run the example "echo\_robot\_state" from libfranka.

Change to the build directory of libfranka and execute the following on Linux:

```
./examples/echo_robot_state <fc>
```

The program will display the current state of the robot on the console and will exit automatically after a few iterations.

```
{
```

```

"O_T_EE": [0.998578,0.0328747,-0.0417381,0,0.0335224,-0.999317,0.0149157,0,-0.04122,
           -0.016294,           -0.999017,0,0.305468,-0.00814133,0.483198,1],
"O_T_EE_d": [0.998582,0.0329548,-0.041575,0,0.0336027,-0.999313,0.0149824,0,-0.0410535,
             -0.0163585,-0.999023,0,0.305444,-0.00810967,0.483251,1],
"F_T_EE": [0.7071,-0.7071,0,0,0.7071,0.7071,0,0,0,1,0,0,0,0.1034,1],
"EE_T_K": [1,0,0,0,0,1,0,0,0,0,1,0,0,0,0,1],
"m_ee": 0.73, "F_x_Cee": [-0.01,0,0.03], "I_ee": [0.001,0,0,0,0.0025,0,0,0,0.0017],
"m_load": 0, "F_x_Cload": [0,0,0], "I_load": [0,0,0,0,0,0,0],
"m_total": 0.73, "F_x_Ctotal": [-0.01,0,0.03], "I_total": [0.001,0,0,0,0.0025,0,0,0,0.0017],
"elbow": [-0.0207622,-1], "elbow_d": [-0.0206678,-1],
"tau_J": [-0.00359774,-5.08582,0.105732,21.8135,0.63253,2.18121,-0.0481953],
"tau_J_d": [0,0,0,0,0,0],
"dtau_J": [-54.0161,-18.9808,-64.6899,-64.2609,14.1561,28.5654,-11.1858],
"q": [0.0167305,-0.762614,-0.0207622,-2.34352,-0.0305686,1.53975,0.753872],
"dq": [0.00785939,0.00189343,0.00932415,0.0135431,-0.00220327,-0.00492024,0.00213604],
"q_d": [0.0167347,-0.762775,-0.0206678,-2.34352,-0.0305677,1.53975,0.753862],
"dq_d": [0,0,0,0,0,0],
"joint_contact": [0,0,0,0,0,0], "cartesian_contact": [0,0,0,0,0,0],
"joint_collision": [0,0,0,0,0,0], "cartesian_collision": [0,0,0,0,0,0],
"tau_ext_hat_filtered": [0.00187271,-0.700316,0.386035,0.0914781,-0.117258,-0.00667777,
                         -0.0252562],
"O_F_ext_hat_K": [-2.06065,0.45889,-0.150951,-0.482791,-1.39347,0.109695],
"K_F_ext_hat_K": [-2.03638,-0.529916,0.228266,-0.275938,0.434583,0.0317351],
"theta": [0.01673,-0.763341,-0.0207471,-2.34041,-0.0304783,1.54006,0.753865],
"dtheta": [0,0,0,0,0,0],
"current_errors": [], "last_motion_errors": [],
"control_command_success_rate": 0, "robot_mode": "Idle", "time": 3781435
}

```

Fig. 10.3: Example output of „echo robot state“

The respective fields are explained in the libfranka API documentation (<https://frankarobotics.github.io/libfranka>.)

### NOTICE

If an error occurs at this point, perform the ping test and verify that FCI is enabled and the robot's brakes are open.

To perform the ping test, enter the following command line:

```
ping <fc1-ip>
```

If this command fails, the robot is not properly connected to the network, or the IP address was not assigned correctly during the setup phase. Please set up the network again according to the steps described in chapter 9.3.1 Network configuration for FCI.

# 11 Safety Concept

The safety concept of Franka Research 3 provides a simple approach to making the robotic system safe within its target application. The system provides a set of safety functions compliant with EN ISO 13849-1. For more information on safety functions, see chapter "

Safety Function".

With the Franka UI tool Watchman, the safety operator can use those safety functions in so-called safety rules and scenarios to cover the risks identified in the risk analysis carried out for the robot cell and application.

The configuration of the safety system through Watchman is split into two parts:

- General safety-relevant settings are configured in the safety setup (e.g., defining the behavior of safe inputs).
- Safety scenarios allow covering different situations with suitable safety measures.

Each safety scenario can define one or more safety rules to cover a certain situation/state the robot can be in.

Each safety rule consists of a safety function, optional selectable conditions (defining when the rule is active), and a reaction triggered when the safety function is violated.

With the safety setup and the safety scenarios, the safety operator can set up the safety system according to the needs revealed by the risk analysis. Franka Research 3 comes with a predefined and pre-----validated set of scenarios. If they are suitable to cover the needs revealed by the risk analysis, this setup can be used out-of-the-box.

If specific safety rules and scenarios are required, the safety operator can adjust predefined scenarios and rules using Watchman. Some safety scenarios are read-only or contain fixed rules to ensure a minimum set of safety measures common to most applications. In general, these presets are defined by ISO 10218-1.

The safety operator must validate all customized safety settings and scenarios before confirming and activating them on the robot.

The predefined safety scenarios cover the possible operation states of the system.

## NOTICE

During recovery of violated safety functions, the system switches to the predefined recovery scenario to provide a safe recovery. The original scenario (e.g., Work), in which the violation happened, its rules, and especially the violated safety function, are not active during recovery. The system switches back to the original scenario as soon as the recovery has been completed. The integrator must consider the predefined recovery scenarios when performing the application-specific hazard & risk assessment for completed machinery.

## 11.1 Safety Functions

### ⚠ WARNING

#### Hot Surfaces and Guiding during Recovery

At ambient temperatures above 30 °C the robot surface can become too hot to touch. Therefore, in case of occurrence of a safety function violation which requires hand-guiding during recovery, the following must be observed:

- Recovery may be performed only by personnel specifically trained for this situation.

- Before recovery, surface temperatures must be evaluated to be within touchable limits. Cooldown times depend on previous operation and ambient temperatures.
- Wearing heat resistant safety gloves for this procedure is advised.

#### NOTICE

Franka Research 3 distinguishes between two kinds of safety functions: monitoring functions and stopping functions.

Monitoring functions guarantee that limits are not breached, e.g. speed (SLS-J), position (SLP-C)...

Stopping functions are triggered upon a monitoring violation or a safety input. It is the Safety Operator's obligation to consider stopping times and stopping distances when configuring the limits.

#### NOTICE

Connecting external devices with a separate power supply may jeopardize the system's safety function if the electrical ratings are not complied with.

In addition, the voltages in the connected devices must either be SELV or suitably isolated from system-connected signals.

## Safe inputs

Name	Description	Safety Rating	Stop Reaction
X3.1 - Emergency stop	The X3 connector in the robot base provides one safe input to connect an emergency stop.	PL d / Cat.3	Category 1 stop
X4 - External Enabling	The X4 connector at the robot base provides one safe input dedicated to a 3-position External Enabling Device.	PL d / Cat.3	Releasing or fully pressing the Enabling Button activates the SMSS safety function. The reaction in case of a violation of SMSS depends on the active safety scenario.  Operating mode "Programming": Category 1 stop (see predefined scenario "Idle") Operating mode "Execution": Reaction depending on SMSS configuration in scenario "Work."  During safety function violation or error recoveries, fully pressing or releasing the Enabling Button triggers a Category 1 stop.
Enabling Button	A 3-position Enabling Button is provided near the flange on the Pilot-Grip of the robot.	PL d / Cat.3	
X3.2 - Safe input 1 X3.3 - Safe input 2	The X3 connector on the robot base provides two additional safe inputs. The behavior of those two inputs can be configured in the safety setup.	PL d / Cat.3	Depends on the configuration in safety scenarios.

## Monitoring functions

Name	Abbreviation	Description	Safety Rating	Recovery in case of violation
	When SLP-C is activated, the robot cannot be controlled by FCI!			
Safely Limited Cartesian Position	SLP-C	<p>Monitoring of the Cartesian position of certain points on the Arm. The position is checked against user-defined Cartesian area.</p> <p>The following points are monitored:</p> <ul style="list-style-type: none"> <li>• Flange</li> <li>• Elbow</li> <li>• Wrist</li> <li>• Customer defined tool spheres</li> </ul> <p>The monitoring can be configured to signal violation either when one or more points are inside the defined space or when one or more points are outside the defined limits.</p> <p>Parameterization:</p> <ul style="list-style-type: none"> <li>• End Effector model (up to five spheres) <ul style="list-style-type: none"> <li>◦ Radius of each sphere</li> <li>◦ Position of each sphere center relative to the flange</li> </ul> </li> </ul> <p>Hint: This is a general setting and will affect all safety functions using this tool model.</p> <ul style="list-style-type: none"> <li>• Monitored Cartesian space (box)</li> <li>• Violation if inside/outside</li> </ul>	PL d / Cat.3	<p>Violated position or orientation limits will be shown in Desk of Franka UI.</p> <ul style="list-style-type: none"> <li>• Unlock brakes of robot.</li> <li>• Guide robot out of Cartesian position limit. Franka UI shows if position limits are not violated anymore.</li> <li>• Finish recovery by pressing Confirm in Desk.</li> </ul>
	When SLS-C is activated, the robot cannot be controlled by FCI!			
Safely Limited Cartesian Speed	SLS-C	<p>Monitoring of the Cartesian speed of certain points on the Arm structure. The following points are monitored:</p> <ul style="list-style-type: none"> <li>• Flange</li> <li>• Elbow</li> <li>• Wrist</li> <li>• Centers of customer-defined tool spheres</li> </ul> <p>Parameterization:</p> <ul style="list-style-type: none"> <li>• Limit for Cartesian speed</li> </ul>	PL d / Cat.3	<p>A violation of the speed limit is shown in a dialog in the Franka UI.</p> <ul style="list-style-type: none"> <li>• Confirm violation by pressing the button in Pop-up message.</li> </ul> <p>No further recovery procedure is necessary.</p>
Safely Monitored Stand Still	SMSS	<p>Monitoring of the standstill in Cartesian space of certain points on the Arm structure. The following points are monitored:</p> <ul style="list-style-type: none"> <li>• Flange</li> <li>• Elbow</li> <li>• Wrist</li> <li>• Centers of customer-defined tool spheres</li> </ul> <p>The user cannot change the parameters of this safety function.</p>	PL d / Cat.3	<p>A violation dialog is shown in the Franka UI.</p> <ul style="list-style-type: none"> <li>• Confirm violation by pressing the button.</li> </ul> <p>No further recovery procedure is necessary.</p>

Safe End Effector Power Off	SEEPO	<p>Safely switch off the power provided to the end effector (48 V power line). The behavior of SEEPO can be configured in the safety setup. E.g., it can be configured that SEEPO switches off the power when an emergency stop is triggered.</p> <p>Parameterization:</p> <ul style="list-style-type: none"> <li>General configuration, whether SEEPO is active or not</li> <li>Switch-off triggers of SEEPO</li> </ul>	PL b / Cat. b	The power of the end effector can be switched on again in Settings or the sidebar of Desk.
-----------------------------	-------	--	------------------	--

## Internal monitoring functions (not parametrizable and configurable in safety rules)

Name	Abbreviation	Description	Safety Rating	Reaction	Recovery in case of violation
<b>NOTICE:</b> The operator can recover all violations.					
	When SLP-J is activated, the robot cannot be controlled by FCI!				
Safely Limited Position of Joint	SLP-J	<p>Monitoring of the position of each joint in joint space.</p> <p>This safety function is only used internally to protect the joint limits of the Arm, prevent self-collisions and local clamping. It is not available in user-defined scenarios.</p> <p>This is a limiting function.</p>	PL d / Cat.3	-	<p>A dialog within Franka UI informs the user about the violation and allows recovery.</p> <ul style="list-style-type: none"> <li>Unlock the joint that shall be moved by clicking the unlock icon in the recovery dialog.</li> <li>To enable recovery motion, press the External Enabling Device.</li> <li>Move the joint by pressing the +/- buttons in the recovery dialog.</li> </ul> <p>Hint: Joints in a violated state can only be moved away from violated limit. All other joints can be moved in both directions to move the robot into a more convenient pose.</p>
Safely Limited Speed of Joint	SLS-J	<p>Monitoring of the speed of a single joint in joint space.</p> <p>This internal safety function is used, e.g., to prevent fast motions during joint position recovery.</p>	PL d, Cat. 3	Cat. 1 Stop	<p>A violation dialog is shown in Franka UI.</p> <ol style="list-style-type: none"> <li>Confirm violation by pressing the button.</li> </ol> <p>No further recovery procedure is necessary.</p>
Safely Limited Distance	SLD	<p>SLD monitors a single joint to stay within a permitted position window.</p> <p>This internal safety function is used, e.g., to prevent excessive motion during the brake opening procedure.</p>	PL d, Cat. 3	Cat. 1 Stop	<p>A safety error dialog is shown in the Franka UI.</p> <ol style="list-style-type: none"> <li>Acknowledge error by pressing the button.</li> </ol> <p>No further recovery procedure is necessary.</p>

## Stopping functions

Name	Description	Safety Rating
------	-------------	---------------

Category 0 stop	The Arm is stopped immediately by removing power from the motors and applying the brakes.	PL d / Cat.3
Category 1 stop	The Arm is stopped in a controlled manner using the normal control of the motors until the standstill of each joint. The brakes are applied, and the power is removed from the Motors upon standstill. The Cartesian speed deceleration is monitored.	PL d / Cat.3
Category 2 stop	The Arm is stopped in a controlled manner using the normal control of the motors until the standstill of each joint. Upon standstill, the standstill is safely monitored. The Cartesian speed deceleration is monitored.	PL d / Cat.3

## Safe outputs

Name	Description	Safety Rating
Safe End Effector Power Off	Switch the power provided to the end effector (48 V power line) off.	PL b / Cat.b

## Further safety ratings

The 3-stage Enabling Button near the robot's flange is realized in compliance with IEC 60204-1:2016 and IEC 60947-5-8:2006.

The 3-stage External Enabling Device provided by Franka Robotics is realized in compliance with IEC 60204-1:2016 and IEC 60947-5-8.

The Emergency Stop provided by Franka Robotics complies with IEC 60204-1:2016 and EN ISO 13850:2015.

## 11.2 Other safety-related recoveries (in case of safety errors)

### Joint position error recovery

Only Safety Operators can recover joint position errors.

A dialog in Franka UI informs the user about the error and allows recovery.

Detailed instructions on how to correct the error can be found in Chapter 8 Troubleshooting.

### Safe input error recovery

Safe input errors are recoverable by confirming the respective dialog in Franka UI if confirmation for those inputs is configured in Watchman.

### Other safety errors

Other safety errors are typically not recoverable. Please try to restart the system to recover from such errors. If the error persists, contact your vendor or Franka Robotics.

### General info for all cases

- In case of a safety violation, the robot does not allow motion until the recovery has been accomplished.
- In case of a safety violation, the base flashes slowly in red.
- If necessary, Franka UI will show a recovery wizard to perform the recovery procedure.
- Only the safety operator can recover joint position errors.

- The operator can perform all other recoveries.

### NOTICE

Further measures for possible troubleshooting are described in chapter 11 please refer to the respective **Hardware Manual** (i.e. **Franka Research 3 Arm v1** or **Franka Research 3 Arm v2**).

## 12 SAFETY CONFIGURATION/WATCHMAN

### 12.1 Watchman

Watchman is a tool in the Franka Web User Interface (Franka Web UI) for displaying, creating and editing safety functions also on the Franka Research 3. Safety functions can be defined via rules. These rules can in turn adapt the behavior of the respective scenarios, such as "Teach" and "Work", to the required protective measures from the risk assessment for the two operating states of the robot ("Programming" and "Execution").

The safety configuration can only be done by a Safety Operator. The Safety Operator is one of three user roles available on FRANKA RESEARCH 3. The other roles available are Administrator and Operator. See the chapter 7 "ROLES AND PERSONNEL" for more information. A user in the Administrator role can create a Safety Operator role but cannot edit any safety functions himself. Only in the user role Safety Operator can modify settings in Watchman. The Safety Operator is responsible for the correct safety configuration and documentation of the safety functions and should only be performed by qualified personnel.

#### 12.1.1 Overview

In Watchman, the security scenarios are displayed via an intuitive graphical interface.

The structure of the interface is illustrated and described below.




Figure 54: Watchman

In the header of the Watchman view, you can find the currently valid security configuration report on the right. The button with the three dots on the right allows you to reset the security configuration to factory settings.

The current validation status of the safety configuration is displayed. Green means validated; orange indicates the need for validations

Clicking the validation symbol next to the Draft tab displays the checksum of the currently validated safety configuration.

In the left part of the view, a structural overview is visible, which displays the validation states of the basic safety settings as well as those of the different safety scenarios.

In the editing area, the basic settings or the rules of the safety scenarios are displayed.

The security scenarios are divided into editable and non-editable security scenarios.

The detailed descriptions of the security scenarios can be found in [Chapter 10.1 Safety Concept in this Manual](#).

The editable scenarios are used for the possibility to adapt the robot control to the determined safety measures from the previous risk analysis. The following scenarios are available:

- Work
- Assist
- Test & Jog
- Teach

For the "Work" and "Assist" scenarios, up to 16 user made safety rules can be created and configured. In the "Test & Jog" and "Teach" scenarios, only adjustments to the existing rules can be made.

The factory settings of the Franka Research 3 have a predefined and prepared set of scenarios. If these are suitable for the requirements identified in doing the risk analysis, they can be used immediately.

#### NOTICE

By default, the "Work" scenario in Watchman does not contain any rules. To ensure a safe operation also considering the application-specific risk & hazard analysis the empty "Work" scenario is not pre-validated. A safety operator has to setup the system correctly and validate the safety settings.

Non-editable safety scenarios (Read Only Scenarios) are safety functions permanently integrated in the robot Control that ensure safe and standard-compliant operation of the robot and cannot be changed. These are:

- Idle
- Opening/Closing Brakes
- Position Error Recovery
- Position Function Recovery IDLE
- Position Function Recovery
- Joint Limit Recovery
- Work Invalid

All recovery scenarios as well as the scenario "Work Invalid" are scenarios that are only activated in the robot state "error/violation". The robot states "error/violation" is caused by violations of the safety scenarios from the robot states "execution" and "programming" or in the presence of a fundamental safety-relevant error.

The robot state "execution" includes the scenarios "Work", "Assist" and "Opening/Closing brakes". The robot states "programming" includes the scenarios "Idle", "Teach" and "Test and Jog".

## 12.2 Safety Configuration

With the Franka UI tool Watchman, the safety operator can use those safety functions in so-called safety rules and scenarios to cover the risks identified in the risk analysis carried out for the robot cell and application.

The configuration of the safety system through Watchman is split into two parts:

- General safety-relevant settings are configured in the safety setup (e.g., defining the behavior of safe inputs).
- Safety scenarios allow covering different situations with suitable safety measures.

Each safety scenario can define one or more safety rules to cover a certain situation/state the robot can be in.

Each safety rule consists of a safety function, optional selectable conditions (defining when the rule is active), and a reaction triggered when the safety function is violated.

### 12.2.1 Adjusting predefined scenarios and rules

If specific safety rules and scenarios are required, the safety operator can adjust predefined scenarios and rules using Watchman.

Some safety scenarios are read-only or contain fixed rules to ensure a minimum set of safety measures common to most applications. In general, these presets are defined by ISO 10218-1.

The safety operator must validate all customized safety settings and scenarios before confirming and activating them on the robot.

The predefined safety scenarios cover the possible operation states of the system.

During recovery of violated safety functions, the system switches to the predefined recovery scenario to provide a safe recovery.

The original scenario (e.g., Work), in which the violation happened, its rules, and especially the violated safety function, are not active during recovery.

The system switches back to the original scenario as soon as the recovery has been completed.

The integrator must consider the predefined recovery scenarios when performing the application-specific hazard and risk assessment for completed machinery.

### 12.2.2 Safety Scenarios for states in Programming mode

#### Idle (read-only)

- The user might be close to the robot but not interact with it. The robot is at a safely monitored standstill.
- This is the default state in Programming mode if no other mode is active or if conflicting inputs are present.

#### Teach (customizable)

- The user can hand-guide the robot.
- Safe activation signal: Pressing the Enabling Button located on the Pilot-Grip.
- The safety operator can customize the pre-defined velocity limit.

#### Test & Jog (customizable)

- The user watches and verifies the execution of a created task and inches the robot via Franka UI.
- Safe activation signal: External Enabling Device (X4).
- The safety operator can customize the pre-defined velocity limit.

## Opening/closing brakes (read-only)

- Active while the brakes are opened or closed.
- Extend of motion and speed is safely limited.

### 12.2.3 Safety Scenarios for states in execution mode

#### Work (customizable)

- The robot works independently by executing a task.
- This scenario is pre-filled with rules activating the safely monitored standstill (SMSS) safety function stopping the robot when the inputs X3.2 or X3.3 are opened. A rule to trigger the "Safely Monitored Standstill" within "Work" to allow a switch to the "Assist" mode must be set.
- The safety operator can customize all rules within this scenario.

#### Assist (customizable)

- Collaborative operation "hand-guiding" as defined by ISO 10218-1 while in execution mode.
- Safe activation signal: Pressing the Enabling Button located on the Pilot-Grip while the robot is in Safely Monitored Standstill.
- The safety operator can customize the velocity limit for this mode and/or add custom rules.

#### Opening/closing brakes (read-only)

- Active while the brakes are opened or closed.
- Extend of motion and speed is safely limited.

### 12.2.4 Error/Violation states

The following states are not active in the normal operation of the robot. They only become active when safety functions in the other states are violated, or safety-relevant errors occur.

#### 12.2.4.1 Work invalid (read-only)

If there is no valid safety scenario available for the Work mode, the "Work invalid" scenario is activated as a backup to prevent the robot from moving.

#### 12.2.4.2 Violation idle (read-only)

This state is active after any safety function is violated and the respective reaction has been carried out.

#### 12.2.4.3 Recovery (position error, joint limit violation, or space violation) (read-only)

This state is active while the robot is recovering from a violated safety function or an error.

Safe activation signal: Depending on the type of violation or error.




Figure 55: States during normal operation

Robots must always be surrounded by protective devices that prevent people from entering the hazardous area or, in the case of collaborative robots there are safe-zones that must be initiated and monitored when people are present in the hazardous area.

After the risk assessment has been carried out, the safety scenarios of the robot must be adapted to the determined necessary safety functions of the worksite in which the robot system is installed.

The Franka Research 3 is delivered with a predefined and pre-validated set of safety scenarios according to the requirements from the ISO 10218-1 standard.

If the risk analysis shows that these are sufficient, the Franka Research 3 can be integrated and used in the planned working environment of the robot without further changes to the safety configuration after appropriate electrical integration. However, if the risk analysis shows that additional safety functions are required, these must be implemented in Watchman by means of rules that apply in specific robot states or scenarios.

## 12.2.5 Editing of the Safety Configuration

In order to complete the following steps, a "Safety Operator" user must be logged in.

Open the Watchman interface via the menu on the sidebar in Franka UI. The active and confirmed rules as well as the validation states of the scenarios are now displayed on the Watchman interface.




Figure 56: Validated rules

Switch to "Draft" mode and start editing.




Figure 57: Switch to "Draft" mode

After opening a validated safety concept in "Draft" mode, all validation markers are shown in green.

## Safety Concept




Figure 58: Draft Mode

If changes are now made, the validation markers of the changed safety function and all parameters, rules and scenarios dependent on the change, as well as the overall safety, are shown in orange. Parameters, rules and scenarios that are not affected remain validated and thus green.




Figure 59: Validation markers

After completing the safety configuration, the overall concept must be validated. The procedure is described in the chapter "Validate".

## 12.3 Import/Export of Safety Settings

Safety configuration can be exported and imported. Alternatively, a complete backup can be created using the PDF export option.

## Safety Concept

The import/export feature allows safety operators to transfer safety settings between systems or create backups. It will allow users to avoid the need to configure settings from scratch, ensures uniform safety settings across multiple systems and provides a way to back up current safety settings for recovery purposes.




Fig. 12.7: Import/Export settings

### Scenarios for Using This Feature

#### System Migration:

- When moving safety settings to a new system.

#### Backup and Recovery:

- For safeguarding settings against data loss.

#### Multiple Systems:

- Applying the same settings across different systems to maintain consistency.

### Post-Import Actions

Safety operators can export the currently committed safety settings into a file that they can download onto their own device. Subsequently, this file can be imported on the same system or on a different system. In both cases, the currently existing drafts are overwritten with the contents of the imported file.

After importing settings, the safety operator should:

- Check the new settings to ensure they are correct.
- The safety operator still needs to commit these drafts before the imported safety settings become active.
- In case the import was performed on a different system, additionally they also need to be validated before they can be committed.

#### NOTICE

It is crucial to ensure that any important drafts are committed or backed up before proceeding with the import.

### 12.3.1 Import Procedure

#### 1. Open Standard UI:

Start by opening the Standard UI Watchman.




Fig. 12.8: Standard UI Watchman

#### 2. Access Top Right Menu:

Click on the menu located at the top right corner of the interface.




Fig. 12.9: Import settings as drafts

#### 3. Select "Import Settings as Drafts":

In the top right menu, find and click on the "Import Settings as Drafts" tab.

#### 4. File Selection for Import:

A prompt will appear asking you to select a file for import. Choose the appropriate file from your system.

## Safety Concept




Fig. 12.10: File selection

### 5. Warning Dialog:

After selecting the file, a warning dialog will appear. It will inform you that your current drafts will be replaced with the safety settings from the import file.




Fig. 12.11: Warning dialog

### 6. Confirm Import:

If you confirm the action, the safety settings will be successfully imported.

### 12.3.2 Export Procedure

To export current committed settings:

#### Steps:

1. Navigate to the "Export committed settings" section in the Watchman UI.
2. Select the settings to export.
3. Download the file.

#### File Format

**NOTICE**

The only permitted file extension is. fesafety. Manual modification of these files is not allowed.




Fig. 12.12: Safety settings imported

### 7. Error Handling:

If there is an error during the import, an error message will appear stating "Safety settings could not be imported." This error typically occurs if the safety rules file has been manipulated.




Fig. 12.13: Error Message

### 12.3.3 Safety Setup

In the Safety Setup, the higher-level configurable basic settings of the robot are mapped. These include the areas "General Safety Settings", "Safe Input Configuration" and "End Effector Configuration".

With the safety setup and the safety scenarios, the safety operator can set up the safety system according to the needs revealed by the risk analysis. Franka Research 3 comes with a predefined and prevalidated set of scenarios. If they are suitable to cover the needs revealed by the risk analysis, this setup can be used out-of-the-box.




Figure 60: Safety Setup

### 12.3.4 General Safety Settings

To be able to operate the robot in Assist Mode, the "Enable Assist Mode" checkbox must be set. The description of the Assist Mode can be found in the chapter "4.3.2.3". If this function is deactivated, the Assist function is not available in any other submenus of the robot Control. These function menus are then greyed out.

This function is activated in the default settings of the robot.

### 12.3.5 Safe Input Configuration

The processing of the safety inputs X3.2 and X3.3 can be configured via the Safe Input Configuration.

Form information on the assignment of inputs X3.2 and X3.3 **please refer to chapter 7 section 7.6 Wiring and Electrical Installation in the respective Hardware Manual (i.e. Franka Research 3 Arm v1 or Franka Research 3 Arm v2).**

With the setting "No confirmation required", the signal is processed directly. The control reacts immediately to the input.

With the setting "Confirmation required", the signal is processed directly when the contact is opened, but a query message appears on DESK when the input is closed. This message must be confirmed in order to process the input signal internally.

In the default settings of the robot, the setting "No confirmation required" is preselected.

### 12.3.6 End Effector Configuration

The safety behavior of the connected end effector is defined via the "End Effector Configuration". The following fields can be set:

- **Description:** Free editable description of the end effector
- **SEEP0 Behavior:** Determination of when and for which safety shutdowns the end effector is to be switched off.




Figure 61: End Effector Configuration

- Safety Error: => Robot safety fault
- Safety Error /EM-Stop:=> Robot safety fault or Emergency Stop
- Safety Error/EM-Stop/Cat. 1 stop: Robot safety fault or Emergency Stop or Category 1 Stop
- Safety Error/EM-Stop/Cat. 1&2 stop: Robot safety fault or Emergency Stop or Category 1 or 2 Stop

In the default settings of the Robot is set "Safety Error/EM-Stop/Cat. 1 stop".

**Power ON Behavior:** Setting when the end effector is to be switched on.

- **Manual** => with each switching on, the end effector must be activated manually in DESK.
- **Automatic** => the end effector will be automatically activated when the joints are unlocking.

In the default settings of the Robot „Automatic“ is preselected.

### 12.3.7 Creation of spheres for modelling an End effector envelope

When an end effector is mounted, the control system needs information on its dimensions in order to be able to monitor the end effector spatially and kinetically. For this purpose, up to five spheres can be created and placed in their size and position so that the totality of the spheres resembles the contour of the end effector.

For spatial monitoring, the outer shells of the spheres are considered and for velocity monitoring, the centers of the spheres are considered. It should be noticed that spheres placed far from the end effector flange can be very sensitive to velocity monitoring due to the lever consideration.

When positioning the spheres, ensure that the Franka hand is mounted at a 45° angle to the flange coordinate system.

## Safety Concept




Figure 62: Configuration of spheres

Below, an example of the sphere configuration of the Franka Hand is shown.




Figure 63: Example of spheres for Franka Hand

If your gripping situation is not covered by the spherical model shown above, it must be adapted. Make sure that contours that could lead to collisions are covered by the sphere model. If you are handling longer objects, the maximum speed of

## Safety Concept

cantilevered objects must also be monitored. To do this, you can place the centers of the spheres at the ends of the object. The maximum speed is monitored in the centers.




Figure 64: Example of sphere configuration Franka hand with staff

### 12.3.8 Creating and editing rules

Up to 16 rules can be created in each of the "Work" and "Assist" scenarios. By clicking on "Create Rule" below the last rule displayed, a new rule is inserted. By clicking on the "Delete" symbol within a rule, it can be deleted.

A screenshot of the Watchman software interface. The top navigation bar includes 'DESK', 'WATCHMAN', 'SETTINGS', 'Language EN-English', '192.168.0.193 Auto Cell #3- IP 0.193', and 'safety-operator jane\_doe'. The main area is titled 'Safety setup' and shows 'EDITABLE SCENARIOS' with 'Work' selected. It displays two rule configurations: 'Rule 1' (Activation Space: Everywhere, Safety Function: Maximum speed, Reaction: Cat. 1 Stop) and 'Rule 2' (Activation Space: Everywhere, Safety Function: Safe Monitored Standstill, Reaction: Cat. 2 Stop). Both rules have a 'Configure' button and a 'Last Modified' timestamp. A red box highlights the 'Create Rule' button at the bottom of the rule list. The left sidebar lists 'READ-ONLY SCENARIOS' including 'Idle', 'Opening/Closing Brakes', 'Position Error Recovery', 'Position Function Recovery Idle', 'Position Function Recovery', 'Joint Limit Recovery', and 'Work Invalid'.

Figure 65: Editing rules

### 12.3.9 Structure of a rule

The rule consists of the following components:




Figure 66: structure of a rule

- **Name:** Freely editable name of the rule
- **Activation Condition:** Condition for which the rule is activated. The following selection is possible:
  - Always the rule is always active
  - X3.2 the rule becomes active, when the two-channel X3.2-Input is opened.
  - X3.3 the rule becomes active, when the two-channel X3.3-Input is opened.
- **Activation Space:** Spatial area in or outside of which the rule gets active. The following selection is possible:
  - Everywhere the rule is active in the whole working area of the robot.
  - Inside / Outside Area the rule becomes active inside or outside a free definable cuboid space. When defining the space, it is determined whether the rule becomes active inside or outside the space.
- **Safety Function:** Safety function to be executed when the rule is violated. The following selection is possible:
  - Always violated no safety function is executed. If "Always violated" is selected, the rule is permanently violated if the rule becomes active.
  - Inside/Outside Area a violation is triggered if the robot is inside or outside a defined space. When defining the space, it is determined whether the violation should take place inside or outside the space.
  - Maximum Speed Within the applicable spatial area of the rule, the maximum speed is monitored. If the speed of the robot exceeds the permitted maximum speed, a monitored reduction to the permitted speed takes place. If the reduction of the speed does not occur as expected, the preselected reaction is executed (Cat. 1 Stop / Cat. 2 Stop).
  - Safe Monitored Stand Still In the applicable spatial area of the rule, the robot is safely monitored for standstill. Any movement leads to violation of the rule.



## WARNING

NOTICE that control of the robot via FCI is not possible when the SLP-C, SLS-C or SLP-J functions are active. This affects the safety functions that include spatial position monitoring (Inside/Outside Area) and Cartesian speed monitoring (maximum speed). If these are integrated into rules in Watchman, control via FCI is not possible.

- **Reaction:** Reaction of the robot that is executed when the rule is violated.

- Cat. 1 Stop Category 1 stop in accordance with EN ISO 13849-1 (controlled stop and shutoff of energy when standstill is reached)
- Cat. 2 Stop Category 2 stop according to EN ISO 13849-1 (controlled stop with maintenance of energy)

The robot Control already takes the rules into account during the execution of the movement and thus always tries to avoid violations. If a violation cannot be prevented, the safety function initiates the safe reaction.

Functions or parameters that need to be validated are shown in the rule window with the validation symbol. If the rule is validated, this symbol is green. If validation is required, this symbol is orange.

If "Inside/Outside area" is selected in the "Activation Space" or "Safety Function" field of a rule, this area must be configured by clicking on the "Configure" button that appears. The following view opens.




Figure 67: Configuration of "Activation Space"

With the selection field "Type of area" you can determine whether the robot is not allowed to leave the cuboid area (stay inside area) or not allowed to enter the cuboid area (stay outside area). The tool, flange, wrist and elbow are monitored here.




Figure 68: monitoring

To define the cuboid area, its reference corner must first be determined. To do this, you can guide the TCP of the robot to the reference corner and teach the position values by clicking on "Take from Robot" or enter the position values manually. In case of manual entry, the coordinates are entered in the coordinate system of the robot.

The reference corner must be selected in such a way that the opposite corner is created with positive values only. Then the spatial extension must be defined by entering the XYZ values. For this purpose, the space can also be taught by guiding the robot TCP to the opposite corner point.

With the help of "Orientation", the defined space can also be rotated around the three axes. The pivot point is the set reference corner.




Figure 69: Creating cuboid area

When the cuboid area has been defined, the settings must be saved. Then the validation button becomes active. After clicking on "Validate", the validation specifications and the entered values are compared. The robot must now be moved

in all 3 directions in and out of the created space. Depending on whether "Stay inside area" or "Stay outside area" is selected, "Violated" appears with a red dot if the function is violated. This can be used to check whether the area boundaries correspond to your specifications.

After the check has been done, the area is confirmed by clicking on "Confirm Validation". Next to the button, the validation is then confirmed in green and after returning to the rule, the validation symbol of the rule parameter appears in green.

If "Maximum Speed" is selected in the "Safety Function" field of a rule, this area must be configured by clicking on the "Configure" button that appears. The following view opens.




Figure 70: Setting of speed

The maximum permissible speed determined from the risk assessment must be set and confirmed by clicking on "Save". The entry must then be validated by clicking on "Validate".

After validation of the set speed, the validation must be completed by clicking on "Confirm Validation".

Next to the button, the validation is confirmed by a green symbol and after returning to the rule, the validation symbol of the rule parameter appears in green.

### 12.3.10 Validate

After changes have been made to the settings in Watchman, validation must take place. The structure of Watchman is such that rules only need to be validated if an included parameter has been changed and a scenario only if an included rule has been changed.

## Safety Concept




Figure 71: Validation structure




Figure 72: Validating

Non-validated rules are indicated by the orange validation icon in the lower right corner. To validate a scenario, click on "Validate Rules" above the listed rules.




Figure 73: Validating of rules

All rules of the scenario are now listed with the respective parameters. In the first step, the rule parameters and then the rule itself must be validated in the unconfirmed rules, as described previously. The procedure for validating the various safety functions is described below:

#### 12.3.10.1 **Validating safe inputs**

- Check whether the activation condition matches the safety concept defined by the risk analysis.
- Connect peripheral devices to safe input.
- Check whether the status displayed in the Watchman UI changes when the input is triggered.

#### 12.3.10.2 **Validating SLP-C**

- Check whether the parameters of the safety functions correspond to the safety concept defined by the risk analysis.

#### 12.3.10.3 **Validating SLS-C**

- Guide the robot in Programming mode so that the defined rules are violated.
- Check that the violation state displayed next to the safety function in the Watchman UI changes when the rules are violated at the expected positions/orientations.

#### 12.3.10.4 **Validating SEEPO**

- Check that the power supply to the end effector is switched off in all expected situations.

#### 12.3.10.5 **Validating the entire rules, scenarios and overall configuration**

- Check whether the parameters of the safety functions correspond to the safety concept defined by the risk analysis.
- Check at each level whether the combination of activation triggers, safety functions, reactions, rules and scenarios correspond to the safety concept defined by the risk analysis.

To validate the rule, click on "Confirm Validation" or check the box next to the rules to be confirmed and then click on "Confirm Selected Rules" above the rules.

## Safety Concept

All rules are now displayed as validated.

The next step is to confirm the security scenario by clicking on "Confirm Whole Security Scenario". The Watchman overview is now displayed again and the security scenario that has just been confirmed is now shown as validated.

All scenarios that have not been validated must be treated within the manner described above.

After all scenarios have been validated, the "Report & Commit" button appears in the upper left corner.




Figure 74: Validating Watchman

Click on "Report & Commit". The security report opens, which is generated from Watchman settings.

This report contains all the relevant information for documenting the security functions, including the generated checksum.

The report must now be printed and signed.




Figure 75: Safety Report

By subsequently checking the box "I verify that I signed the report" and then clicking on "Commit", it is confirmed that the report has been printed and signed.

The security configuration is now saved and accepted in the system. The validation symbol next to the slide switch is now displayed in green and shows the validated state.

By clicking on the validation symbol next to the slide switch, the current checksum of the security configuration is displayed.

## 13 ROBOT LED INDICATOR SYSTEM

### 13.1 Overview of the status indicators

Status lights on both sides of the base take on the corresponding color, similar to a traffic light. The status lights will flash slowly during boot-up, when Franka Research 3 requires attention, or when the user enters values. The lights are lit in the corresponding color of the Franka Research 3 status during other processes. A circular status light in the middle of the Pilot-Disc indicates Franka Research 3's status as well.

When the operator is interacting with the Arm, the status light on the Pilot-Disc is switched off.

#### **WARNING**

##### **Dangerous and uncontrolled motions of the Arm**

Risk of severe injury, such as crushing, tearing of the skin, and puncturing from the Arm and end effectors.

- Ensure that the end effector and/or the object mass and the Center of Mass (CoM) are parameterized correctly.
- Keep out of the workspace during operation.

#### **NOTICE**

The motion speed in Teach or Hand-Guiding Mode is pre-set. The speed can be reduced according to the risk evaluation of the Arm within its application.

The robot uses six distinct LED colors to communicate its operational status. These lights can appear in two patterns:

- **Solid (Static)** – indicating a stable state
- **Blinking (Flashing)** – indicating a transitional or attention-required state

LED indicators are visible in three key locations:

- Desk Interface
- Base of the Robot
- Pilot (Control Handle)

Each color and pattern combination provides critical information about the robot's current state and whether it is safe to interact with. These visual cues are designed to enhance operator awareness and safety.

## 13.2 LED Activation Behavior

- **Base LEDs:**  
Always active. They continuously reflect the robot's operational status and are the primary reference for system state.
- **Pilot LEDs:**  
Only active during programming or manual guidance. They provide feedback specific to user interaction during these modes.

## 13.3 Startup Checklist for Operators

When powering on the robot, always:

1. Verify that all indicator lights are functioning properly.
2. Ensure the LEDs are clearly visible from your working position.
3. Interpret the lights correctly to determine whether the robot is:
  - a. IDLE or in TEACH mode
  - b. Executing a task
  - c. In an error or warning state
  - d. Awaiting user input

### Important Safety Considerations

(\*) Whether it is safe to approach the robot in each state depends on the application-specific risk and hazard analysis and the configured safety scenarios. While LED indicators help identify the robot's state, they are not certified safety functions.

If in doubt, always use appropriate safety measures before approaching the robot:

- Press the Emergency Stop
- Activate a Protective Stop
- Confirm the robot is in a safe state via the user interface

## 13.4 Flashing Patterns

Pattern	Frequency	Meaning
Slow Flashing	~0.6 Hz	Indicates a transition between states or a request for user attention
Fast Flashing	~2 Hz	Warns that motion is initiating, the robot is moving slowly, or the system is updating

**Error and Communication Loss**

If the controller loses communication, this is treated as a critical error and is signaled with a solid red light.

## 13.5 LED Priority Logic

- The LED system always displays the most critical state.
- If multiple events occur simultaneously, the color with the highest significance is shown.
- Within the same priority level, only a one-color scheme is displayed at a time to avoid confusion.

## 13.6 LED Color Reference Table

Category	LED Color	LED Pattern	Status Meaning	User Action
Robot System Status	White	Static	System idle or in TEACH mode.	 Observe standard safety precautions before approaching.
	White	Slow Flashing	Booting or shutting down.	 Do not interrupt. Wait until complete.
	White	Fast Flashing	System updating.	 Do not unplug or interrupt. Wait until complete.
Brakes	Yellow	Static	Brakes locked/unlocked.	 Used during brake operations.
	Yellow	Slow Flashing	Waiting for the boot to finish.	 Wait until solid yellow or next instruction.

Category	LED Color	LED Pattern	Status Meaning	User Action
Warnings	Yellow	Static	Warning state.	 Do not approach. Check UI.
	Yellow	Slow Flashing	Warning: user interaction needed.	 Check UI and acknowledge warning.
Safety Errors	Red	Static	Severe errors (e.g., safety, system, communication).	 Do not approach. Investigate via UI.
	Red	Slow Flashing	Safety violation or application error.	 Check UI. Approach only if safe and trained.
	Red	Fast Flashing	Error recovery in progress.	 Wait or reset via UI.
	Red	Slow Flashing	Input needed to recover from error. Error recovery possible with user input (e.g., joint limits exceeded during hand-guiding)	 Unlock joint or reset to resume operation.
Execution	Green	Static	Task executing autonomously.	 Do not approach. Robot is moving.
	Green	Fast Flashing	Execution will begin shortly (e.g., FCI countdown).	 Do not approach. Execution imminent.

Category	LED Color	LED Pattern	Status Meaning	User Action
Collaborative	Green	Slow Flashing	Task active in assist mode.	 Approach with care. Follow safety protocols.
Execution Mode	Blue	Static	Execution phase ready. Brakes engaged.	 Approach with care. Robots may start moving.
	Blue	Slow Flashing	Brakes opening or collaborative mode (no active task).	 Robot may move slightly. Safe to approach.
	Blue	Slow Flashing	Execution interrupted. Awaiting feedback.	 Provide feedback to resume. Robot paused.
Conflicts	Magenta	Static	Conflicting input detected (e.g., manual guidance vs. automation).	 Do not approach. Resolve input conflict.
	Magenta	Slow Flashing	Input needed to resolve conflict.	 Provide input or guidance to continue.

## 14 SERVICE AND SUPPORT

### NOTICE

If you have purchased your Franka Research 3 at one of our sales partners or if you have cooperated with a service provider, please get in contact with them first. Our partners can consolidate information and reach out to Franka Robotics for troubleshooting and further support.

Please visit [www.franka.world](http://www.franka.world) for supplemental material and additional information on our robot.

For any other requests regarding service and support please contact us at [support@franka.de](mailto:support@franka.de). We will issue a ticket regarding your request in our service and support center and our experts will respond as soon as possible.

When contacting our service, please have the following information available:

- ✓ Customer no.
- ✓ Serial no. of the Control
- ✓ Serial number of the Arm
- ✓ Log files of the system

### 14.1 Rescue System

In case the Control does not boot, or an administrator login is not possible, a rescue system is implemented in the Control.

Only basic functions for accessing the Control are supported in the rescue system. These functions can be:

- the retrieval of system logs for further error analysis with the customer,
- retrieving the configuration of the network setting of the Rescue System,
- the reinstallation of the system version by synchronization with Franka World,
- resetting the main system to factory settings.

Robot movements or other interactions with the Arm or end effector are not supported.

To access the Rescue system user interface, connect an operator device with access to a browser to the X5 port on the Arm base via an Ethernet cable.

To manually boot the Control into the Rescue System, perform the following steps:

- ✓ Shut down the Control, wait for the fans to switch off, then switch off the main switch.
- ✓ Wait approx. 10 sec. before restarting the Control by switching on the main switch.
- ✓ Wait at least 20 sec., but less than 40 sec.
- ✓ Switch off the Control with the main switch.
- ✓ Wait 10 sec.
- ✓ Restart the Control by switching on the main switch.

The Control should now boot into the rescue system. After calling up the [robot.franka.de](http://robot.franka.de) web interface on the connected user device, the following user interface is displayed in the browser.

## SERVICE AND SUPPORT




Figure 76: Rescue System

## Network

The Rescue System tries to use the stored network settings of the main system. If this fails, the default settings are used.

On this page you can temporarily adjust the network settings of the Control. The settings only apply temporarily within the Rescue System and are not adopted in the main system after a restart.




Figure 77: Network

## System

On this page you can start a download of the log-file or initiate the factory reset.




Figure 78: Log Download and Factory Reset

- **Log Download**

When downloading logs, the Rescue System collects the log files of the main system. If the file system of the main system is corrupted, this operation may fail.

- **Factory Reset**

The factory reset function resets the main system. All configurations and created tasks as well as all installed apps and functions are deleted. This has no effect on the Rescue System itself. After the reset, the system must be restarted by the user.

### Franka World

This function allows you to reinstall or update the system software of the main system. Installing apps and features is not possible in the Rescue System.

To ensure an error-free installation of the system software, all apps and features are deleted during this type of installation.

After successful installation and booting of the main system, all apps and features can be reinstalled in the main system via the Franka World page. However, previously created tasks can only be restored if they have been saved or backed up separately before.




Figure 79: Franka World

### Exiting the Rescue System

To exit the rescue system, the Control must be restarted. The Control then restarts in the regular system.

## 14.2 Log download

The FR3 system collects information while it is running and forwards this data to the user through specific log files. Currently, there are four different log files where this information is gathered and provided.

## 14.3 Available log files and how to download them

The four different log files include:

Log file	Description	Specific to
System log package	It contains all log files that are specific to the system, readable only by Franka Robotics employees. These logs are used for trouble shooting system issues. It is recommended to include system logs when creating a support ticket.	Franka Robotics employees
Safety log	It contains all safety-related events of the system. This log is human-readable and will never be deleted, even during a factory reset.	Franka Robotics employees, integrators, and end users
Cyclic log data	It contains data collected while the robot is active, such as forces and velocities.	End users, and Franka Robotics employees

Event log data	It contains all event-based data, including restarts and system updates.	End users
----------------	--	-----------

## 14.4 Downloading log data

Log data can be downloaded in Settings for each of log files.

- **System log package, cyclic log and event log:** These can be downloaded under Settings -> System.




Figure 80: System

- **Safety log:** This can be downloaded under Settings -> Safety.




Figure 81: Safety/ Download

- **Desk API:** All log files are also available via the Desk API.

## 14.5 Hardware Exchange

In case of damage to the Control unit or the Arm, it may be necessary to carry out a replacement of the respective defective component.

## 14.6 Replacing the Control

In the case of a failed Control unit, two situations must be considered.

1. Control can still be started and can connect to Franka World.
2. Control can no longer be started and/or synchronized with Franka World.

For the situation where the Control still starts and can connect to Franka World, all installed features and apps can be detached from the defective Control via Franka World and made available in Franka World for transfer to the new Control. To do this, follow the steps below:

1. Perform a backup of the Control as described in chapter 14.5 "BACKUP".
2. Call up Franka World via the URL <https://franka.world>.
3. Switch to the "MANAGE" view in the menu bar. All Control units registered to you, or your company, are now listed here.
4. Select the Control unit of concern. All system information of the robot as well as the features installed on the Control are displayed.




Figure 82: Device detail view

By removing the blue checkmarks, the respective features are marked for detaching from the Control. Before removing all blue check marks, take a screenshot or NOTICE which features were installed on the Control.

5. After the blue check marks have been removed, the "Synchronized" button appears with a blue check mark. Clicking it initiates the detachment from the Control and executes it with the next synchronization of the Control.
6. Now call up the URL <https://franka.robot.de> in the browser and select "Settings" in the Desk menu.

7. Open the Franka World view. You will now see that changes are to be made to the robot. Click on "Download" to download the changes. It is also possible to manually import the update file into the system.




Figure 83: Sync-prompt

8. After reading the update data, the "DISCARD" and "APPLY" buttons appear. To apply, click on "APPLY".
9. Depending on the change, the system may reboot. After completion, "Everything up to date" appears in the view.




Figure 84: Everything up-to-date

The license affiliation of your features and apps are now detached from the old Control and are available for linking in Franka World.

10. Now replace the old Control with the new one. To do this, follow the steps described in Section 16.2.1 "Replacing the Control".
11. Switch on the new Control and open the Desk interface via the URL <https://franka.robot.de> after starting the system.
12. Switch to the "Settings/Franka World" view and perform the registration by clicking the "REGISTER" button. Once registration is complete, you can configure your Control in Franka World.




Figure 85: Register Control

13. Open the URL: <https://franka.world> in the browser and log in.
14. switch to the MANAGE view and check whether the new Control is displayed.
15. Select the new Control and open the view by clicking on it.
16. You will now see the data of the new Control and all the features available in your account.
17. According to the screenshot or your NOTICEs of the old Control, fill in all information fields and select the features by setting the respective checkmark.
18. Click on the "SYNCHRONIZED" button to apply the data.
19. Now switch to the Desk view of the robot in the browser by entering the URL <https://franka.robot.de> and call up the "Settings/Franka World" view there.
20. The changes that you have activated in Franka World are now displayed. Click on "DOWNLOAD".
21. After all data has been downloaded, you can accept the transfer by clicking on "APPLY". The Control now installs all changes and carries out a restart if necessary.
22. To restore your Control to the status of the old Control, restore the system from the backup data of the old Control. Proceed as described in chapter 14.5 "BACKUP".

For the situation that the Control can no longer be started and thus synchronization with Franka World is no longer possible, the licenses of the old Control must be detached from the defective Control by the support of Franka Robotics GmbH.

To do this, send an e-mail with the following information to Support at: [support@franka.de](mailto:support@franka.de):

- Account name (Franka World)
- Account-number (Franka World)
- Serial number of the defective Control
- serial number of the new Control (optional)
- Type of Platform (FP3/FR3)

After the licenses have been released by Support, they will be available again in Franka World for linking to a new Control.

Now connect the new Control to the Arm and then switch it on. To transfer the features and apps, proceed as described in steps 13 to 22. If you still have an update of the old Control, you can import the data into the new Control according to the procedure described in Chapter 7.3 “Updates”.

## 14.7 Transportation pose of the Arm

### 14.7.1 Procedure

1. Log onto the user interface in Franka UI.
2. Click on Settings.
3. Navigate to System.
4. Depending on the Execution mode
  - a. In Programming: Click and hold-to-run the “Move to pack pose” button.
  - b. In Execution: Click the “Move to pack pose button” and wait until the motion has finished.

*The Arm will automatically move to the transport pose while the button is pressed. If the robot is in Programming mode, pressing the enabling device is also necessary to move the robot.*

#### NOTICE

The system monitors the connection of the Franka UI hold-to-run control with a maximum timeout of 1 s. If a connection loss is detected while hold-to-run control is pressed, the system is stopped.

## 15 INDEX

Administrator.....	19	Franka Control Interface.....	20, 33, 35
Apps .....	30, 47, 88, 89	FCI.....	20, 33, 35
Axes.....	78	Franka UI.....	22
Backup .....	53	Franka World.....	16, 46, 113
End Effector Configuration .....	55	Managing Apps and Updates.....	47
Modbus Configuration .....	54	Guiding	
Network Setting .....	54	Guiding / hand-guiding .....	22
Safety Configuration.....	58	Guiding Button .....	82, 98
Saving of the created Tasks .....	55	Guiding Mode .....	92
Cartesian.....	25	Idle.....	22, 23, 82
Cartesian space.....	77	Integrator .....	17
Center of Mass (CoM) .....	98, 106	Log Download.....	113
Collaboration space.....	86	Operating Modes .....	82
Enabling Button .....	22, 95, 98	Operator.....	17, 21, 22, 25
<b>End effector.....</b>	<b>16, 98</b>	Pose.....	77
factory reset .....	19	Practical Tips for Usage and Positioning .....	94
Factory Reset.....	113	Responsible person.....	17
Fail-safe Locking System.....	98	Roles and Personae	
Fieldbus .....	81, 83	Administrator .....	18

## INDEX

Roles and Personae	
Administrator	18
Assigning user roles	18
Integrator	17
Operator	17
Responsible person	17
Safety operator	18
Safety	
Safe inputs	24
Safe outputs	26
Safety Concept	21
Safety Functionalities	24
Safety rules	21
SEEPO	25
Service and Support	98, 111
Hardware Exchange	122
Settings-Schnittstelle	15
Single Point of Control (SpoC)	78
SLD	26
SLP-J	26
SLS-C	25
SLS-J	26
SMSS	25
Stopping functions	26
Category 0 stop	26
Category 1 stop	26
Category 2 stop	26
Switching Off	105
Task	32, 78, 89
Teaching	90, 97, 98
Teaching a Task	90, 97
Tracking error	96
Troubleshooting	98
User interface	18
Watchman	14, 21
Creating and editing rules	71
Creation of spheres for modelling an End Effector envelope	68
Editing of the Safety Configuration	60
End effector configuration	68
General Safety Settings	67
Safe Input Configuration	67
Safety Setup	67
Structure of a rule	71
Validate	74

## 16 TABLE OF FIGURES

Figure 1: language selection initial configuration.....	10
Figure 2: Network .....	10
Figure 3: Franka World registration.....	11
Figure 4: Creating Administrator.....	12
Figure 5: End effector settings .....	12
Figure 6: Control request.....	18
Figure 7: User management waiting for approval.....	18
Figure 8: User request .....	19
Figure 9: Enforce control .....	19
Figure 10: Overview operating modes.....	21
Figure 11: Procedure .....	22
Figure 12: Area assignment.....	23
Figure 13: Work operation .....	24
Figure 14: Assist operation.....	26
Figure 15: Indication of Assist Mode.....	26
Figure 16: Conditions for motion enabling in Assist Mode.....	27
Figure 17: App parameterization.....	30
Figure 18: App interface .....	31
Figure 19: Pose fine adjustment.....	32
Figure 20: Overview of switching between Hand-Guiding-Modes .....	33
Figure 21: Illustration of Hand Guiding.....	33
Figure 22: Settings, if "User mode" is selected.....	34
Figure 23: Hand guide approval .....	35
Figure 24: Test & Jog.....	37
Figure 25: Message "A joint limit has been violated" .....	55
Figure 26: Message with display of the faulty joint .....	55
Figure 27: Confirmation joint is back in the limit.....	56
Figure 28: Message "Joint position error detected" .....	56
Figure 29: Message with display of failed joints .....	57
Figure 30: Joint recovery locked .....	57
Figure 31: Joint recovery ready for movement.....	58
Figure 32: Conformation position reached .....	58
Figure 33: Confirmed Joint recovery.....	59
Figure 34: Message Button not held .....	59
Figure 35: Message if reference position not reached .....	60
Figure 36: Confirm the complete recovery .....	60

## INDEX

Figure 37: Franka UI .....	38
Figure 38: Download User Manual.....	39
Figure 39: Desk.....	40
Figure 40: Desk Sidebar .....	42
Figure 41: Watchman .....	43
Figure 42: Menu Settings.....	43
Figure 43: Managing Apps and Features via Franka World.....	48
Fig. 0.2: Network connection of control.....	49
Figure 45: Managing of Updates via Franka World.....	50
Figure 46: Network Settings .....	52
Figure 47: Save Tasks .....	53
Figure 48: Schematic overview FCI .....	62
Figure 49: Network connection for FCI Usage .....	67
Figure 50: Network settings.....	68
Figure 51: Values.....	69
Figure 52: Ubuntu – setting a static IP.....	69
Figure 53: TUI-Interface.....	72
Figure 54: Watchman .....	81
Figure 55: States during normal operation.....	85
Figure 56: Validated rules.....	86
Figure 57: Switch to “Draft” mode.....	86
Figure 58: Draft Mode.....	87
Figure 59: Validation markers.....	87
Figure 60: Safety Setup.....	92
Figure 61: End Effector Configuration.....	93
Figure 62: Configuration of spheres.....	94
Figure 63: Example of spheres for Franka Hand.....	94
Figure 64: Example of sphere configuration Franka hand with staff.....	95
Figure 65: Editing rules.....	95
Figure 66: structur of a rule.....	96
Figure 67: Configuration of "Activation Space" .....	97
Figure 68: monitoring .....	98
Figure 69: Creating cuboid area .....	98
Figure 70: Setting of speed .....	99
Figure 71: Validation structure.....	100
Figure 72: Validating .....	100
Figure 73: Validating of rules .....	101
Figure 74: Validating Watchman.....	102
Figure 75: Safety Report.....	102

## INDEX

Figure 76: Rescue System.....	109
Figure 77: Network.....	109
Figure 78: Log Download and Factory Reset .....	110
Figure 79: Franka World .....	111
Figure 80: System.....	112
Figure 81: Safety/ Download.....	112
Figure 82: Device detail view.....	113
Figure 83: Sync-prompt .....	114
Figure 84: Everything up-to-date.....	114
Figure 85: Register Control .....	115

Franka Robotics GmbH  
Frei-Otto-Straße 20  
80797 Munich  
Germany

